AMERICAN CINEMATOGRAPHER

The Motion Picture CAMERA Magazine

JANUARY,
1935

Price 25c

THE PICTURE TELLS THE STORY

DU PONT NEGATIVE

DU PONT

REG U.S. PAT. OFF.

DU PONT FILM MANUFACTURING CORPORATION

35 WEST 45TH STREET
NEW YORK CITY

PLANT . . . PARLIN, N. J.

SMITH & ALLER LTD.
6656 •• SANTA MONICA BLVD.
HOLLYWOOD, CAL.

THE DU PONT TRADE MARK HAS NEVER BEEN PLACED ON AN INFERIOR PRODUCT

AMERICAN CINEMATOGRAPHER

A Technical and Educational publication of motion picture photography

Published monthly by the
AMERICAN SOCIETY
OF CINEMATOGRAPHERS INC
6331 Hollywood Boulevard
Hollywood, California

Telephone GRanite 2135

JOHN ARNOLD, President, A S C
GEORGE SCHNEIDERMAN Treasurer, A S C

Volume 16 JANUARY, 1935 Number 1



What to Read

CREATING Moods with Light
by Victor Milner, A S C 7

EXPLAINING Technicolor 3-Color Process
by W Stull, A S C 8

PHOTOGRAPHY of the Month 10

THE DIN Scale
by Martin Blitz 11

Next Month

● John Seitz will talk about Rhythm with Light Mr Seitz is considered one of the outstanding cinematographers of the industry This will be the second in a series of articles on the artistic side of cinematography as practiced by the leading cinematographers in Hollywood This month Victor Milner talked on Mood in Lighting Mr Milner gives a glimpse of what the ace cinematographer aims at when shooting the present-day picture

● There will be other articles in our next issue The Cinematographer with Father Hubbard on his latest expedition will tell you of his experiences

The Staff

EDITOR
Charles J VerHolen

TECHNICAL EDITOR
Emery Huse, A S C

ASSOCIATES
Walter Blanchard
Karl Hole

CIRCULATION MANAGER
M Miller

ADVISORY EDITORIAL BOARD
Victor Milner, A S C
Chas G Clark, A S C
Hatto Tappenbeck, A S C
Jackson J Rose, A S C
Fred Gage, A S C
Dr J S Watson, Jr , A S C
Dr L M Dieterich, A S C
Dr L A Jones, A S C
Dr C E K Mees, A S C
Dr W B Rayton, A S C
Dr Herbert Meyer A S C
Dr V B Seese A S C

FOREIGN REPRESENTATIVES
Georges Benoit 100, Allee Franklin Pavillions-sous Bois France Seine Telephone LeRaincy 13 19 H T Cowling 4700 Connecticut Ave , Washington D C

NEW YORK REPRESENTATIVE
S R Cowan 19 East 47th St New York City Phone Plaza 3 0483

ESTABLISHED 1918 Advertising Rates on application Subscription U S $2 50 a year, Canada $3 50 a year Foreign $3 50 a year Single copies 25c Foreign single copies 35c

COPYRIGHT 1935 by American Society of Cinematographers Inc

Neither the American Cinematographer nor the American Society of Cinematographers is responsible for statements made by authors This magazine will not be responsible for unsolicited manuscripts

MEMBERS**

Directors of Photography

Abel David
Andersen Milford A
Andriot Lucien
Arnold John
Ash, Jerome H
August Joseph
Barlatier, Andre
Barnes George S
†Bell Chas E
†Benoit, Georges
Boyle, Chas P
Boyle, John W
Brodine Norbert F
Brown, Jos S, Jr
Chancellor, Philip
Clark, Dan
Clarke Charles G
Cline Robert E
Corby Francis
Cronjager, Edward
Crosby, Floyd D
Daniels William H
†Davis, Charles J
Depew Ernest S
DeVinna, Clyde
Dietz, Wm H
†Dored John
Draper Lauran A
*Dubroy Joseph A
†DuPor E B
Dyer, Edwin L
Dyer Elmer G
Edeson Arthur
Fernstrom, Ray
Fischbeck, Harry
Folsey George J Jr
Freulich Henry
*Freund Karl
Gaudio, Gaetano
Gerstad, Merritt B
Gilks, Alfred
Glennan, Bert
Good Frank B
Haller Ernest
Halperin Sol
†Harten Charles
†Herbert Charles W
Hickox, Sid
Hickson John T
Howe James Wang
Hunt, Roy
Jackson Harry
†Jonsen, William H
Jennings, J D
June Ray
Kershner, Glenn
Kline Ben
†Knechtel Lloyd
Kohler, Henry N
Krasner Milton
Kull, Adolph E
Lancaster, George J
Landers Sam
Lang Charles B Jr
Lloyd Art
Lundin Walter
Lyons Chet
McCord Ted
McGill Barney
Mackenzie Jack
-MacWilliams Glenn
Marley J Peverell
Marsh Oliver
Marshall Chas A
Marshall, William C
Martinelli, Arthur
Marzorati Harold J
Mate Rudolph
Meehan Geo B Jr
Mellor, William C
Miller, Arthur
Miller, Ernest W
Miller, Virgil E
Milner, Victor
Morgan, Ira H
Musuraca Nick
Neumon, Harry C
Nobles, William
O Connell, L William
Overbaugh, Roy F
Polmer Ernest
†Paul, Dr Edward F
Peach Kenneth
Perry Harry
Perry, Paul P
Polito, Sol
Rees William A
Reynolds Ben F
Robinson George
Rose Jackson J
Rosher Charles
Rosson Harold
-Ruttenberg Joseph
Schneiderman George
Schoenbaum Charles
Seitz John F
Shamroy Leon
Sharp Henry
*Sheorer Douglas
Siegler, Allen
‡Silver, John
‡Sintzenich Harold
*Smith, Jack
Smith, Leonard
Snyder Edward J
Sparkuhl Theodor
‡Steiner, William, Jr
Stengler Mack
Stout Archie J
Strenge, Walter
Struss, Karl
Stumar, Charles
Stumar, John
Tetzloff Ted
Thompson, William C
Todd Arthur
Toland, Gregg
Tover, Leo
Towers, Richard
Tutwiler, Tom
Valentine, Joseph A
*Van Buren Ned
Van Enger, Willard
Van Trees James
†Varges Ariel
von Sternberg, Josef
Wagner Sidney C
Walker Joseph
Warren Dwight
Warrenton, Gilbert
Wenstram, Harold
Wetzel Al
White Lester
Wyckoff Alvin
†Zucker Frank C

Special Process

Binger Ray
Cully Russell A
Edouart Farciot
Fabian Maxmillian
Haskin Byron
Jackman Fred
Jackman, Fred Jr
Kelley, W Wallace
Kaenekamp, H F
Lipstein Harold
Pollack Gordon
Ries Irving C
Walker, Vernon L
Williams William N
Wrigley Dewey
Wimpy Rex
Zech, Harry

Operative Cinematographers

Anderson Don
Anderson Wesley
Arling Arthur E
Badaracco Jacob
Bader Walter
Ballard Lucien
Bell Jack C
Bennett Guy M
Bennett Monroe
Bentley Fred
Biroc Joe
Blackstone Cliff
Bradley Wilbur H
Burks Robert
Campbell, Arthur
Chewning, Wallace
Clark Roy
Clemens, Geo T
Cline Wilfrid E
Cohen, Edward J
Collings Russell D
Cooper, Harry H
Cortez Stanley
Davis Harry
Davis Leland E
Dean, Foxon
DeGrasse, Robert
Diamond, Jos R
Dunn, Linwood G
Eagler, Paul
Eslick LeRoy
Fapp Daniel L
Feindel Jockey
Fetters C Curtis
Fitzgerald Edward
Golezio, Len
Golligon Thomas
Garnett Paul
Gertsmon Maury
Gibbons Jeff T
Glassberg Irving
Gordon James
Gray, King D
Green Kenneth
Greene Al M
Griggs Loyal
Guffey, Burneff
Guthrie Carl
Hallenberger, Harry
Harper, James B
Henderson, Edword
Hoag Robert
Huggins, L Owens
Jennings Lewis E
†Kelly Wm J
Knatt James
Kornman Anthony
Lone, Al L
Lonning Reggie
LoShelle Joseph
Laszlo Ernest
Lawton, Charles C
Lindon Lionel A
Lynch, Warren
Lyons, Edgar H
Mayer, Fred
Meode Kyme
Merland Harry
Metty R L
Mols Pierre M
Newhard, Guy J
Newhard Robert S
Nogle Geo G
Novak Joe
Palmer, Robert
Pierce, Otta
Pittack, Robert
Pyle Edward
Ragin, David
Ramsey Ray L
Rand William
Redmon, Frank
Reed Arthur
Ries Ray
Roberts, Albert G
Roberts Irmin
Roberts Josiah
Robinson Walter C
Scheurich Victor
Schurr, William F
Salerno Charles, Jr
Schmitz John J
Schoedsack G F
Shiphom Berf
Smith William Cooper
Snyder Wm
Stafford Earl
Stine, Clifford R
Topoenbeck Hafta
Thompson Stuart
Titus Frank
Travis N C
Ulm, William R
Unholz George
Vaughan Ray V
Vogel Paul Charles
Vogel Willard I
Wester Carl
White, Ben
Wild Harry
Wilky, Guy L
Williams Al E
Williomson, James

Assistant Cinematographers

Abbott L B
Abramson Melvin
Adams Eddie
Ahern, Lloyd
Anderson Eddie
Baldwin, Herold
Barth Willard
Beckner Neal
Bergholz Emmett
Bessette Raoul
Boggs, Haskell
Bourne George
Bradford, William
Brandenburg, Gentry
Bridenbecker, Milton
Brigham, Donald H
Bronner Robert
Burgess Frank
Burke Charles
Caldwell, John C
Carter Ellis W
Clothier William H
Cohon Ben
Cohen Sam
Collins, Edward C
Crawford, Lee
Cronjager Henry Jr
Crouse, John
Curtiss Judd
Daly, James
Dalzell Arch R
Davenport, Jean L
Davis, Mark
Davis, Robt D, Jr
Daval, Richard S
Dowe, Harry
DeAngelis, Louis
de Cozstellaine, Paul
Deverman Dale
Diskant George
Dodds, Wm
Darris Joe
Dowling, Thomas L
Dugas, Frank
Eagan J P
Eckert John
†Etro, Jack
Farley, Joseph L
Fischer, Herbert J
Flinsky Roy
Foxall William
Fredricks, Ellsworth
Garvin, Edward
Gaudio Frank, Jr
Geissler, Charles R
Gerstle, Arthur
Gough Robert J
Grand, Marcel
Greer, John
Haas, Walter
Hackett, James C
Haddow, Ledger
Harlan, Russell
Hayes, Towne D
Higgins James Calman
Higgs, Stuart P
Hill Paul
Haffman Roswell
†Halcombe, Walter B
Harsley Davis S
Hunter Kenneth
Ivey, Jesse F,
Kauffman, R King Jr
Kearns, Edward
Keller Alfred S
Kelley George F
Klein Irving
Kluznik Matt
Lackey Walter K
Lane Art
Laraby Nelson
Leahy, Chas P
Lewis C L
Lockwood Paul
Love Cecil
Lykins, Vollie Jae
McDonald, Frank
McEdword Nelson C
MacDonnell, Stanley
MacIntyre Andy
Martin John
Marble, Harry
Mautina Bud
Meade, Kenneth
Mehl John
Molina Luis
Morena Robert C
Morris Thomas C
Noble Roy
Norton Kay
Orsotti, Alfred
Parkins Harry
Ramsey H Clark
Ronkin Walter
Reinhold Wm G
Rheo Robert
Riley William
Roe Guy
Sanford, S A
Sargent Don
Scheving Albert
Schuch William
Shirpser, C
Sharr Lester
Slifer Clarence
Sloane James
Smith H C
Soderberg, Edward F
Southcott Fleet
Straumer E Charles
Strong, Glenn
Strong, William M
Tolmie Rod
Tripp, Roy
Ulm William R
Van Trees, James, Jr
Van Warmer, John Pierce
Ward Lloyd
Weiler John
Weissman Leonard
Wellman, Harold
Wendall, Jack E
Whitley William
Worth Lothrop

Still Photographers

Allon Ted
Alsop George
Anderson Bert
Bachroch Ernie
Bjerring Frank
Blanc, Harry
Breau Joseph F
Bredell, Elwood
Brown Dalton
Coburn Roberf
Cooper John
Cronenweth, W E
Crosby Warner N
Ellis John
Estep, Junius D
Evansmith, Henry
Farrell, David H
Fraker W A
Freulich, Roman
Fryer, Elmer
Grimes William H
Head, Gordon G
Hendrickson, Fred S
Hommel Geo P
Hopcraff N John
Johnson Ray L
Julian Mac
Kahle Alexander
Kling, Cliftan
Kornman, Gene
Lippman Irving
Lobben C Kenneth
Langet, Goston
Longworth Bert
Lynch, Bert
Manott, S C
Marinold Mirkey
Martin Shirley A
McAlpin, Hal A
Miehle, John J
Osborne Harry
Richardson, C E
Richee Eugene R
Robbins, Leray S
Rowley, Les
Sibbald, Merritt J
Six Berf
Tanner Frank
Van Pelt Homer
Walling, Will J
Welbourne, Chas Scaff

Portrait Photographers

MacDonald Melvin A

Honorary Members

Mr E O Blackburn
Los Angeles Calif
‡Mr George Eastman
Rochester N Y
‡Mr Thomas A Edison
Orange N J
Mr Albert S Howell
Chicoga Ill

Associate Members

Mr Louis A Bonn
Mr George Cove
Dr L M Dieterich
Mr Fred Gage
Mr Emery Huse
Dr Lloyd A Jones
Dr C E K Mees
Dr Herbert Meyer
Mr Hollis Mayse
Dr W B Raytan
Dr V B Sease
Dr J S Watson, Jr

Inactive Members

Cowling Herford T
Dunning Dodge
DuPont, Max B
Fildew, William
Glouner Martin G
Graham Stanley
Horne Pliny
Jackman Dr Floyd
Lockwood J R
Roos, Len H
Stull, William

*Membership by Invitation only **Directors of Photography in Executive Positions -Non Resident Members ‡Deceased

THE NEW SUPERPAN NEGATIVE FILM

• The film industry has long been in position to welcome a new super-sensitive panchromatic NEGATIVE FILM, refined to meet the increasing demands of picture taking.

Agfa Ansco offers the new Superpan Negative, a film of *super-sensitive speed* and a *finer grain*

In both exposure and development the Agfa Superpan Negative gives, through a *wider latitude*, a wider range of pictorial possibilities in motion pictures.

A *non-abrasion* surface coating protects the emulsion physically The *anti-halation* coating underlying the emulsion preserves the photographic definition

High, evenly balanced *color sensitivity* simplifies the problem of correct registration under any lighting conditions, permitting any desired color emphasis with a relatively low multiplying factor for the filter used.

C. KING CHARNEY, Distributor for

AGFA 35mm NEGATIVE *and* POSITIVE FILM

HOLLYWOOD
6372 Santa Monica Blvd
Tel Hollywood 2918 2919

for the **UNITED STATES**

NEW YORK
245 West 55th Street
Tel Circle 7 4635

Agfa

Made in America by **AGFA ANSCO CORPORATION**
FACTORIES AT BINGHAMTON N Y

THE AMERICAN SOCIETY OF CINEMATOGRAPHERS was founded in 1918 for the purpose of bringing into closer confederation and cooperation all those leaders in the cinematographic art and science whose aim is and ever will be to strive for pre-eminence in artistic perfection and technical mastery of this art and science. Its purpose is to further the artistic and scientific advancement of the cinema and its allied crafts through unceasing research and experimentation as well as through bringing the artists and the scientists of cinematography into more intimate fellowship. To this end its membership is composed of the outstanding cinematographers of the world with Associate and Honorary memberships bestowed upon those who, though not active cinematographers, are engaged none the less in kindred pursuits, and who have, by their achievements, contributed outstandingly to the progress of cinematography as an Art or as a Science. To further these lofty aims and to fittingly chronicle the progress of cinematography, the Society's publication, The American Cinematographer, is dedicated

AMERICAN SOCIETY OF CINEMATOGRAPHERS

OFFICERS

JOHN ARNOLD	President
VICTOR MILNER	First Vice-President
JOHN W. BOYLE	Second Vice-President
ELMER G. DYER	Third Vice-President
GEORGE SCHNEIDERMAN	Treasurer
FRANK B. GOOD	Secretary

BOARD OF GOVERNORS

John Arnold — Frank Good
John W. Boyle — Fred Jackman
Dan Clark — Ray June
Elmer Dyer — Charles B. Long, Jr.
Arthur Edeson — Victor Milner
George Folsey — George Schneiderman
Alfred Gilks — James Van Trees
Vernon L. Walker

Frederick L. Klay, Executive Business Manager

PAST PRESIDENTS

Philip E. Rosen — Hal Mohr
Gaetano Gaudio — Homer Scott
James Van Trees — John F. Seitz
John W. Boyle — Daniel B. Clark
Fred W. Jackman

HONORARY MEMBERS

Mr. Albert S. Howell
Mr. Edward C. Blackburn

PUBLIC RELATIONS COMMITTEE

John Arnold — Herford T. Cowling
Frank Zucker — Edwin L. Dyer
Charles Bell — Charles W. Herbert
Charles J. Davis — Mack Stanglar
Paul H. Allen — Ross Fisher
George Benoit — John Dored
Glenn MacWilliams — Philip M. Chancellor
Ariel Vorges — W. H. Jonsen
Max B. DuPont

PRODUCTION COMMITTEE

Daniel B. Clark — Elmer G. Dyer
John W. Boyle — Ned Van Buren

MEMBERSHIP COMMITTEE

Charles G. Clarke — Alfred Gilks
George Folsey

ENTERTAINMENT COMMITTEE

John W. Boyle — Frank B. Good
Charles B. Long, Jr. — Varnon Walker
Alvin Wyckoff

WELFARE COMMITTEE

Ray June — James Van Traas
Fred W. Jackman

RESEARCH COMMITTEE

Victor Milner, Arthur Miller, Dr. Herbert Meyer, John Arnold, John F. Seitz, Emery Huse, Dr. L. M. Dietrich

Creating Moods With Light

by
Victor Milner, A.S.C.

LIGHT is the Cinematographer's most versatile tool. With it he can not only make or break his composition, and display his players to advantage or otherwise, but he can attune the audience-mind to any mood, and key the response to any emotional pitch. Intelligent lighting can prepare the audience for any desired dramatic tempo, and create a subconscious, emotional receptiveness that greatly enhances the dramatic value of the production.

It is not enough that a scene be an intrinsically beautiful bit of photography. It is essentially a vehicle for dramatic expression, and every phase of the photography—especially the lighting—should exist for the specific purpose of telling the scene's story. The Cinematographer who strives solely for pictorial effect, and the man who rigidly follows a fixed scheme of lighting for every production both hamper themselves tremendously. Lighting technique should be flexible, changing (even within a sequence) to harmonize with the mood and tempo of the action.

The Cinematographer should train himself to think directly in terms of lighting. He should be able to read a script and from the bare printed outline of a scene, visualize it not merely in terms of action, or even of camera-angles and moves, but in terms of lighting. It is easy enough to read a heavy, dramatic scene which must necessarily be sombre and slow-paced, and understand that it must be photographed in a low key, or to glance over a swift-paced comedy scene, and see that it will require high-key lighting, but the really important thing is to be able to form such a clear mental picture of the light-treatment of a scene that the lighting itself expresses the scene's mood, tempo and character as clearly as do dialog and action.

Picture, for example, this situation: In a bed in a small room, an old man lies dying, beside him sits his wife, who has shared his joys and sorrows for perhaps fifty years, tensely watching, waiting for the crisis. Different individuals, I suppose, would visualize this in different ways, to my mind, it conjures up at once a mental image of dramatic light-effects. I can see the scene lit in a very low key, with only an extremely repressed scale of gradations. The figure in the bed is limned in grayish light, while the motionless figure of the wife is half hidden in shadow—ominous, formless shadows, relieved only by the subdued illumination on the bed-ridden figure. The lighting alone, unaided by dialog or action, could tell the story perfectly. An atmosphere of such dramatic power could be built up by skillfull lighting that the audience would inevitably experience the tense, wordless agony of the situation, and sense the breathless emotion of an actual deathbed.

Before the advent of sound and dialog, 90% of the responsibility of securing the desired emotional effect in such a scene lay in the hands of the Cinematographer. Today, even with the great advantages of speech, vocal inflection, music and sound-effects, it still rests with the Cinematographer whether the scene shall be merely a well-acted scene, or a gripping emotional experience. The true test of Cinematography is the emotional and dramatic effect it would convey if viewed without the assistance of the sound-track.

To a very limited extent, changes in the mood and tempo of lighting may be brought about by increasing or decreasing the actual amount of light used, but the most essential factors in producing such effects should be judicious manipulation of the lighting-balance, and of the diffusion used on both camera and lights. My personal preference is to minimize the diffusion introduced photographically, and to substitute controlled diffusion in illumination. Photographic diffusion is, at best, an unnatural and unsatisfactory thing, and often the difference in diffusion between a longshot and its correlative close-up becomes physically as well as esthetically a jarring note. The best practice, therefore, is to maintain a fairly constant standard of photographic diffusion throughout, and to manipulate the diffusion in lighting to produce the effects desired.

In the same way, altering the light-diffusion and the beam-concentration is often preferable to substituting larger, smaller or optically different units as the camera-angle changes. A condenser-type spotlight, for example, will give a more intense beam than the average mirror-lamp of the same wattage, and the two are sometimes used interchangeably for certain effects. I have found, however, that the light from the condenser lamp is much whiter, and can be cruelly deceptive when attempting to balance it with other, yellower illuminants, so it is better to use the same unit, altering the diffusing media and

Continued on Page 14



Detail of Three-Color Technicolor Camera
A—Path of light through lens and beam-splitter.
B—Beam-splitter (partially reflecting prism).
C—Green filter in Aperture
D—Magenta filter in Aperture.
E—SuperSensitive film for Green negative
F—Bipack film for Red (rear) and Blue (front) negatives

Explanation

FOR NEARLY forty years it has been acknowledged that natural-color cinematography could not attain widespread commercial success until a really practical three color-component process was developed During that time, innumerable experiments have been made, and scores of patents granted, upon three-color processes, some of which gave excellent results under laboratory test-conditions None of them, however, proved successful under the rigorous test of commercial production None the less, rumors have always been rife that such a process was just around the corner—just short of commercial perfection

For the past decade, these rumors have been justified, for it has been known that the exponents of Technicolor —already successful as a two-color process—were developing a trichromatic process No official hint, however, came from the Technicolor laboratories, where everyone was much too busy solving the laboratory problems of processing two-color films in quantity to make any statements about possible three-color developments

Late in 1932, Technicolor announced that the new three-color process was a fact, and was commercially available Since then, the process has been used in over a score of Walt Disney's "Silly Symphonies," in musical and travel "shorts," and in special color sequences climaxing such productions as "The Cat and the Fiddle," "The House of Rothschild," and "Kid Millions" The three-reel featurette, "La Cucaracha"—a gem of natural-color photography—bids fair to make the industry acutely color-conscious, and the same producers are even now bringing "Becky Sharp" to the screen as the first trichrome feature The process has proven itself in cartoon work, on location, and in the studio every sign (not the least of which is returning box-office prosperity) points to a considerable use of the process in the coming year's more important productions What, then, is Three-Color Technicolor?

Essentially, it is exactly what the name implies a new process of natural-color cinematography which utilizes three, instead of only two, color-components Other than the name, it has very little in common with the older, two-color Technicolor The camera-equipment with which it is photographed is new, and far sturdier than previous color-cameras The results are superior to any previous commercial color-process Most important of all, with the new process comes a basic change in Technicolor's policy toward cameramen

At this point, it may be well to clarify the significance of the term "three-color" process Medical science tells us that the human eye receives its color-impressions through three primary nerve-centers, each of which transmits to the brain one primary color impression The three colors thus received—red, yellow and blue—are termed the primary colors, and all other color-impressions are made up of varying combinations of these three (Green, for example, is a simple overlapping of blue and yellow impressions)

This same principle is the foundation of all forms of natural-color photography and cinematography Obviously, if we make three black-and-white negatives of a scene, recording on one plate all of the red elements, on another, all of the yellows, and on the third, all of the blues, we shall have duplicated the selective action of the three color-sensory nerve-centers of the eye If then we make positive transparencies from the three negatives, toning each in its appropriate hue, and view the three superimposed, we shall have duplicated the resynthetizing brain-action, and should arrive at the same result—an image of the scene in its natural colors

It is by no means easy, however, to apply this principle to photography in a practical way, and applying it to cinematograhy raises innumerable mechanical and technical difficulties—especially if the process is to be used commercially The three separation-negatives must be exposed at the same time, through a single lens The color-filters which must be used to produce these separations absorb a great deal of light, necessitating increased exposure — yet the films must be made at the standard sound-speed of 90 feet per minute The cameras and their optical systems must be of unusual optical and mechanical precision—yet they must be sturdy and simple, as well as being relatively light and portable The laboratory processes should be simple and dependable. The prints must be such as to run on any projector without special equipment this necessitates that the prints be "subtractive," that is, that they have a perfect picture, of standard dimensions, in full color. The question of graininess in large-screen projection rules out the screen-plate method, which has been so successful in still photography

Reducing the number of color-components used from three to two reduces the technical problems proportionately At the same time, a two-color process is more or less color-blind, it gives a fair suggestion of actual color, but it cannot give natural color, since it omits one-third of the primary color-components None the less, every pre-

of the Trichrome Technicolor

by

William Stull, A.S.C.

vious color-cinematography process which has achieved any degree of commercial success has been a two-color process. Nearly all of them have used colors which in some measure have partaken of the missing third. In some instances, red-orange and blue, in others, red and blue-green, or red-orange and blue-green. In any case, the majority of colors have been rendered with more or less distortion, while others simply could not be reproduced. In addition, the two primaries were generally exaggerated to some extent.

Technicolor's two-color process was probably the most successful of the lot, but it, no less than the rest, suffered from partial color-blindness, and the cameras were noisy and delicate. The two images—red-orange and green—were recorded on a single film, which moved at twice normal speed. A single lens was used, and its image was divided by a beam-splitting prism, the red image being reflected to a position one frame below the normal axis, while the green image was two frames above the usual gate. The film was moved two frames at a time, and consumed double footage required for photographing the same action in black-and-white. Printing was either on double-coated positive stock (by a special optical printer) or by the imbibition process. The latter proved the more economical, though at first the results were not satisfactorily uniform, a difficulty now understood to have been overcome. The cameras were excessively noisy, and were not popular with sound-engineers.

The three-color process is in many ways simpler than the two-color method. Three separate films are used, exposed through a single lens, at standard speed. All three are standard types, those receiving the red and green images are standard SuperSensitive Panchromatic, while the blue is recorded on the familiar red-ortho. All three are hypersensitized in the Technicolor plant.

The optical system is simplicity itself. Standard Cooke lenses are used (recalibrated by Technicolor). Behind the lens is a simple beam-splitter, which reflects 2/3 of the light from the lens through an aperture to the left, placed at right angles to the normal position, and passes the remaining 1/3 straight through to a normal aperture. This latter aperture is fitted with a green filter, and a green record is made on regular SuperSensitive film at that point. The second aperture is fitted with a magenta filter (transmitting blue and red light), behind which moves ordinary bipack film. The red-ortho film which forms the front component of the bipack, naturally receives the blue image, its dyed outer surface, in contact with the rear film (SuperSensitive Panchromatic), acts as a red filter, so that this third film receives only the red image. On exterior scenes a light yellow filter is usually placed on the lens, presumably to exclude the ultra-violet and curtail some of the violet, maintaining the proper chromatic balance.

The camera was designed and built by Technicolor, with special Mitchell movements. While it is more silent than many earlier color cameras, the triple-film movement makes it necessary to use the camera heavily blimped for sound work. Naturally, it is considerably larger and heavier than ordinary black-and-white cameras, but not unduly so. It is a decidedly modern design, and definitely built for hard service. The beam splitting optical system—the weak point of previous Technicolor cameras—has been so simplified that it is not only foolproof, but extremely rugged. It can easily be removed, but the design is such that it can only be replaced in the proper manner, and in exactly the right adjustment. The camera-head is box-form in shape, and somewhat reminiscent of several of the silent (black-and-white) cameras lately introduced. Above it are mounted the special 1,000-foot magazines. These magazines are of triple width, to contain the three films, and, unlike conventional magazines, they are loaded from the right-hand side, with the take-up mechanism on the left. Ingress to the two movements is had through three openings—one at each side and one in front. All three must be used in threading the camera. A conventional sunshade and finder are fitted in the customary manner.

Focusing is primarily by scale, for which the lenses are calibrated with unusual accuracy. It is possible, however, to check the focus on a ground-glass screen through an eyepiece at the side of the camera. However, as this screen receives only a small part of the light from the lens, due to the beam-splitter, the image is generally very dim, and it is best to rely on the lens-calibrations for focusing.

Continued on Page 12



View of a Technicolor Three-Color Camera.

PHOTOGRAPHY of the MONTH

"FATHER BROWN, DETECTIVE" (Paramount)

Theodor Sparkuhl, A.S.C.: Directing Cinematographer
Daily Variety (November 21, 1934) · "Theodor Sparkuhl has turned in a fine job with the camera—."
Hollywood Reporter (November 21, 1934). "—well photographed"

"BRIGHT EYES" (Fox)

Arthur Miller, A.S.C.: Directing Cinematographer
Daily Variety (November 22, 1934) - "Photography by Arthur Miller is good"
Hollywood Reporter (November 22, 1934) "Arthur Miller's photography passes with a high mark"

"WEST OF THE PECOS" (Radio)

James Van Trees, A.S.C., Russell Metty, A.S.C.: Directing Cinematographers
Hollywood Reporter (November 22, 1934) "Beautiful photography of the great open spaces provides the last requisite touch"
Daily Variety (November 22, 1934) "—exterior photography by Van Trees and Metty is tops"

"BEHOLD MY WIFE" (Paramount)

Leon Shamroy, A.S.C.: Directing Cinematographer
Hollywood Reporter (November 22, 1934). "Shamray's photography is excellent throughout"

"THE MIGHTY BARNUM"

Peverell Marley, A.S.C.: Directing Cinematographer
Daily Variety (November 22, 1934) "—well photographed'

'STRANGE WIVES" (Universal)

George Robinson, A.S.C.: Directing Cinematographer
Hollywood Reporter (November 24, 1934). "Rabinson's photography is very good"
Daily Variety (November 24, 1934) "—plus fine photography—"

"JEALOUSY" (Columbia)

John Stumar, A.S.C.: Directing Cinematographer
Hollywood Reporter (November 24, 1934). "—and the photography by John Stumor helps considerably"

"FORSAKING ALL OTHERS" (M-G-M)

Gregg Toland, A.S.C., George Folsey, A.S.C.: Directing Cinematographers
Hollywood Reporter (November 26 1934) "—and Gregg Toland's photography adds its particular artistry to the elegant whole"
Daily Variety (November 26, 1934) "Piece is exceptionally well photographed" "Joan Crawford gets from Gregg Toland and George Folsey the best benefit of camera she has had in a long time"

"GRAND OLD GIRL" (RKO)

Lucien Andriot, A.S.C.: Directing Cinematographer
Hollywood Reporter (November 26, 1934) "Photography throughout the picture is okay"

"THE MARINES ARE COMING" (Mascot)

Ernest Miller, A.S.C., William Nobles, A.S.C.: Directing Cinematographers
Hollywood Reporter (November 27, 1934) "Camera work is first class throughout—'.'
Daily Variety (November 27, 1934) "Excellent photography by Ernest Miller and William Nobles —"

"HERE IS MY HEART" (Paramount)

Karl Struss, A.S.C.: Directing Cinematographer
Hollywood Reporter (November 28, 1934) "Photography and mounting are first rate throughout"
Daily Variety (November 28, 1934)! "Some outstanding camera work reflects painstaking effort on the part of Karl Struss"
Motion Picture Daily (November 30, 1934) "Karl Struss' photography embellishes the exquisite backgrounds"

"SWEET ADELINE" (Warner Bros.)

Sol Polito, A.S.C.: Directing Cinematographer
Daily Variety (November 28, 1934). "Sol Polito deserves high praise for handling of the camera"

"THE FIGHTING ROOKIE" (Mayfair)

James Brown, Jr., A.S.C.: Directing Cinematographer
Hollywood Reporter (November 30, 1934) "Good Photography"

"MAN WHO RECLAIMED HIS DEAD" (Universal)

Merritt Gerstad, A.S.C.: Directing Cinematographer
Daily Variety (December 1, 1934). "Photography by Gerstad is excellent—"
Hollywood Reporter (December 1, 1934) "Merritt Gerstad's photography is beautiful throughout, with a few scenes at the beginning of the picture that are standouts of the art"

"HELLDORADO" (Fox)

John Seitz, A.S.C.: Directing Cinematographer
Hollywood Reporter (December 5, 1934) "—and the camera work by John Seitz is very lovely, particularly the scenes shot through cobwebs"

"LOTTERY LOVER" (Fox)

Bert Glennon, A.S.C.: Directing Cinematographer
Hollywood Reporter (December 5, 1934) "Bert Glennon has turned in his usual good photography"

"ENCHANTED APRIL" (Radio)

Edward Cronjager, A.S.C.: Directing Cinematographer
Hollywood Reporter (December 6, 1934) 'Photography very good"

Continued on Page 18



3. Apparatus for making the exposure by the DIN method. The light emerging from the light source (1), behind which is placed a black body (2) passes through diaphragm (3), liquid filter (4), diaphragmed tube (5) to the test strip placed in the dark slide (6) behind the gray wedge. The exposure follows the drawing of the pin (7), whereby the falling shutter (8-9) provided with a slot falls freely and admits light to the plate holder for .05 second. The spring (10) serves as a guide for the shutter which after exposure is raised again by means of the lever (11).

The Din-Scale

New Measure of Photographic Sensitivity

by

Martin Biltz, Dessau*

Translation from Die Naturwissenschaften 21 Oct 13 1933 734-6

THE sensitivity of a photographic emulsion can be characterized in an exact sense only by a great number of exposure steps. In picture photography, however, one desires the sensitivity represented by a single number, where the correct diaphragm setting and exposure time can be chosen from existing exposure meters and exposure tables. In order to accomplish this wish, no efforts were spared during the past century. However, only lately has a practical serviceable method been obtained. In what follows, the sensitometric systems of Scheiner, Hurter and Driffield, Eder-Hecht, used up to the present time for this purpose will be briefly described. Mainly, however, the new system proposed by the Standardizing Committee on Sensitometry of the German Society for Photographic Research, is to be considered.

If it is desired to characterize exactly the sensitivity then the density S produced on a photographic plate after development and fixing must be specified as a function of the intensity of the exposing light (measured in e.g. watts/cm^2), the exposure time, and the wavelength of the exposing light.[2] In order to obtain a single sensitivity number for use in practical exposures, the following simplifications are made. 1. The American viewpoint on this question was recently made public by a report of the research by Davis and Neeland on this point. (Naturwiss. 21, 340, 1933.) 2. $S = \log I_0/I$. I_{II} = intensity of the incident light, I the intensity of the transmitted light.

1. In order to eliminate the complication of the variation of sensitivity with light of varying wavelength in the visible spectrum, the sensitivity is considered for a complex spectrum containing many wavelengths. This simplification is permissible providing that the spectral energy distribution of the light source (for determining sensitivity) is the same as that of the light source for the practical exposure.

2. Either the intensity of the incident light or the exposure time is maintained constant and the dependence of density entirely upon one of these two factors is considered.

3. Among the abscissa values of the density curve (exposure time or light intensity) a single value is chosen as characteristic of the sensitivity. In this manner, a number of the dimensions $\frac{\text{intensity} \times \text{time}}{\text{emulsion surface}}$, which may also be expressed in ergs/cm^2, is obtained.

The above so-called simplifications have been accomplished differently by the different sensitometric systems.

Scheiner accomplished the simplification by employing a Benzin flame, Hurter and Driffield employed burning magnesium ribbon. Of all these light sources, none corresponded in spectral energy distribution to that of the sun, which is the source most often used in practical photography. In comparison with the energy distribution in sunlight, the energy distribution of the lamp used by Scheiner and Hurter and Driffield rises especially high toward the red end of the spectrum, so that a comparison of the speeds of orthochromatic and particularly panchromatic emulsions with the speed of unsensitized emulsions tested with these light sources show a much greater difference than they would for a practical exposure to sunlight. Also the light of burning magnesium ribbon differs greatly in its spectral distribution from sunlight.

The simplification was accomplished by Scheiner and by Hurter and Driffield by holding the light intensity constant. This intensity is defined by the output of the light source. The exposure time is graduated, and in both methods a disk provided with cutout segments placed between the light source and the photographic emulsions admits the light for different lengths of time on different parts of the emulsion. In this manner a time scale is impressed on the emulsion. Eder and Hecht chose the exposure time constant and varied the light intensity by means of a gray wedge placed in front of the photographic emulsion.

The simplification was accomplished in the same manner in the methods of Scheiner and of Eder and Hecht. The sensitivity is characterized by that single exposure time (Scheiner), single light intensity (Eder and Hecht), which produces on the photographic emulsion a density which appears to the eye just higher than the density of a neighboring unexposed point (fog density). The visual determination of this just perceptible density, the so-called threshold value, on the test strip is very uncertain. This

Continued on Page 16

Explanation of the Trichrome Technicolor

Continued from Page 9

The actual operating methods are interesting The lenses are calibrated with a special system of stop numbers totally unlike any of the systems generally used. The maximum aperture of the standard lens used is arbitrarily taken as unity, and numbered 1, the smaller openings bear progressively larger numbers. However, in order to double the amount of light passed at any given opening—No 16, for example—one does not open up to the next smaller number, but halves the indicating digit—in this case, opening to No 8

On all interior scenes, arc lighting is used almost exclusively The method of computing the exposure—which is an even more vital factor than in monochrome cinematography—is unusual A standard Weston illuminometer is used This is a photoelectric light-measuring device, operating on the same principle as the familiar Weston photronic exposure-meter, but more sensitive, and calibrated to read in lower brightnesses This is placed in the position of the subject, and three separate readings are taken one with the photocell pointed directly at the camera, one aiming 45 degrees to the right, and another 45 degrees to the left These are averaged, and this average forms the basis of the exposure calculation If necessary, of course, special readings are taken in shadow areas, and the like, as the exposure latitude of the process is not so great as that of ordinary black-and-white A further important factor is the color of the objects and surfaces being photographed, as the reflectivity of different colored surfaces is more important than in monochrome When working out-of-doors, the illuminometer is fitted with a neutral-density filter, to offset the excess illumination from the sun

Inevitably, natural-color cinematography requires a good deal more light than is normally used in monochrome Exactly how much cannot be said, due to the extreme variations in the lighting technique of individual cinematographers It is understood, however, that photometric measurements r e c e n t l y made by an important observer have shown that the light intensity used for black-and-white cinematography by some cinematographers, and that normally used on sets where three-color Technicolor is being used, a r e v e r y nearly the same Mr J A Ball, Technicolor's Chief Engineer, states that the three-color process requires only a slight increase in illumination over the standard normally maintained for black-and-white by the average "heavy lighter"

However, the process demands much more careful attention to lighting balance than does black-and-white. The lighting must be extremely even, brilliant, but with neither excessive highlights nor shadows The high-lights, especially, must be watched, lest they be "washed out" Back-lighting, while effective, is not generally used in anything like the degree normal in monochrome cinematography In exterior scenes, a three-quarter cross-light seems preferred, though back-lightings, when amply balanced by reflectors or booster-lights, are often very effective Colored light while it plays surprising tricks with the color-rendition of objects upon which it falls, can be extremely effective if intelligently used

It is perhaps expressive of the confidence which the Technicolor authorities have in their new process that they have executed an abrupt about-face in their policy as regards camera personnel Heretofore, it will be remembered, Technicolor maintained its own camera staff of specialized Technicolor Cinematographers, Operatives and Assistants, who were sent to any studio making Technicolor pictures, and had complete physical charge of the camerawork, though the Technicolor Cinematographer usually cooperated with a Directing Cinematographer from the studio's staff in the photographic direction of the film

Now, however, Technicolor's policy is to be different According to Mr. Ball, Cinematographers, Operatives and Assistants from the major studios (and possibly some free-lance Cinematographers of standing, as well) will be invited to the Technicolor plant, and given a special course of instruction in Technicolor cinematography In the end, it is hoped to have a complete Technicolor-trained camera-crew in every major studio, so that when a producer decides to film a production in Technicolor, he will be able to entrust its photography entirely to members of his own staff This policy should be of great benefit to Technicolor, for it will not only develop greater variety and individual style in Technicolor productions, but it will also eliminate the divided responsibility (and its inevitable friction) which seemed inseparable from the old arrangement

According to Cinematographers who have already used the new process, it is extremely easy to master, and very practical Ray Fernstrom, A S C, recently spent several months in Europe, filming travel films in three-color Technicolor for James A Fitzpatrick Travel-talks (MGM release). He states that before he left on the trip, he was able to photograph only 1,000 feet of tests —which constituted his only introduction to the practical aspects of the process Thereafter, he photographed thousands of feet of film, under unfamiliar conditions, with no failures or difficulties of any nature Moreover, he remarks, the camera stood up, not merely under the normal treatment incident to such a tour, but under the fire from tender ministrations of French baggagemen, who do not consider any package set down unless it bounces at least a foot!

The laboratory manipulation of trichrome Technicolor allows at once both more and less control than is usual in ordinary work The three negatives are developed by machine, to a rigidly fixed time A very considerable degree of control is possible in printing, however, not alone over density, but also over the color-balance

The prints are made by the imbibition process In this process, a matrix is made from each of the three color-separation negatives, by printing onto a special film coated with dichromated gelatin instead of the conventional emulsion This is "developed" in warm water, which causes the portions affected by the printing-light—that is, the shadows—to expand, forming a relief image. This matrix is then dyed—each matrix being dyed the **complementary** color of its negative the red negative's matrix being dyed cyanin blue-green, the green matrix, magenta, and the blue matrix, yellow The three matrices are then successively printed in accurate register onto clear film as each matrix has absorbed its dye only in the relief portions of its image (that is, in the shadows), it prints only where the original negative has recorded little or no color, while its complementary-colored matrix prints in the color actually recorded by the first separation-negative (In this stage, incidentally, the word printing is used in the printer's sense, for the matrices print in exactly the same general manner as type.) When the positive has been so printed, and dried, it is complete, and ready for use

During the Technicolor boom of 1929-30, there was a great deal of dissatisfaction with imbibition prints, due largely to the "bleeding" of the colors, to lack of sharpness, and to the absence of uniformity of color The greater part of these difficulties, however, have been overcome, and modern "IB" prints are generally quite pleasingly sharp, with a minimum of bleeding and color-variation

A great deal of control is possible through the processes of matrix-printing, dying and printing, and the density and color-balance can be modified almost as much as is the density of a normal black-and-white print Colors can be increased or decreased; a strictly accurate rendition can be had, or a

Still UNIQUE

WHEN it was introduced in 1931, Eastman Super-Sensitive Panchromatic Negative was definitely a "new and different" product. And there is still no other film like it...no other has wrought comparable changes in motion picture procedure, or contributed as much to motion picture quality. It is only natural that this Eastman film should be unique, also, in the enthusiasm which it continues to arouse among cameramen and producers. Eastman Kodak Company. (J. E. Brulatour, Inc., Distributors, New York, Chicago, Hollywood.)

EASTMAN *Super-Sensitive*
Panchromatic Negative

chromatically distorted one, for special effect, can be produced

At present, the cost for photography and print of trichrome Technicolor is high approximately thrice that of monochrome Naturally, three times as much negative must be used as would be necessary for black-and-white This is understood to cost 7½c per foot Negative developing is stated to cost 2c per foot, while rush printing is priced at 12c per foot, with release-printing figured at 5½c per foot These charges will undoubtedly lower as the volume increases The cameras are, of course, provided on a leasing basis At present, there are nine of the three color cameras ready for use (complete with blimps), and several more are in process of construction With the present policy, no large camera staff will be built up the present staff, possibly slightly augmented, will probably be retained, with, of course, an adequate mechanical staff for repairs, etc, consulting color Art-Directors, and the like· but hereafter, the majority of Technicolor films will be photographed by the men already in charge of camerawork in the major studios

CREATING MOODS WITH LIGHT

Continued from Page 7

beam-concentration rather than substituting a unit of another type The same applies to the "hard" arc-light, which is, however, extremely useful for photographing dead, heavy blacks, such as formal evening dress, for the bluer light of the arc reveals more detail in the black masses than does the more easily absorbed incandescent light

Similarly, it is by far the best practice when working on a sequence in which a definite source-lighting has been established, to adhere closely to this source-light pattern throughout, substituting, perhaps, smaller units, greater diffusion, or less concentrated beams in the closer shots, rather than altering the source-pattern and considering the closer shots as more or less independent of the basic long-shot.

These observations, however, are purely elementary, and have only a rudimentary bearing on the discussion The real art of lighting for mood and tempo must depend primarily upon the individual Cinematographer's artistic sense, and upon his ability to visualize in terms of lighting

Since the majority of Cinematographers have developed this faculty to a marked extent, it would be of incalculable benefit to the Industry if more Producers and Directors made it a rule to consult the Cinematographer earlier in the preparatory stages of production, and to allow him more ample time to familiarize himself with the script before actual filming commences There would result, of course, an immediate commercial advantage gained through more complete pre-production cooperation between the Cinematographer and the Art-Directors and Costumers, in that the physical production and the photography would be better coordinated beforehand, with less need of alterations during actual shooting But mechanical details —while vastly important—are actually secondary to the importance of visualizing the artistic treatment of the production A vital phase of this, incidentally, is the coordination of this treatment with the style and concepts of the Director Given the same script and physical production, two Directors might turn out radically differing productions, each of which would demand basically different photographic treatment, to suit the differences in dramatic mood, tempo and general conception The story of "Cleopatra," for example, might have been interpreted in innumerable different ways by different Directors. one might have chosen to concentrate upon the purely emotional phases of the character, while another might have made **Cleopatra** herself of secondary importance to Caesar and Antony In either case, the photographic treatment—especially the style of lighting — would have to be basically different Cecil De Mille, in his recent production of the story, which I photographed, emphasized yet another angle the fact that Cleopatra was essentially a "showman," who instinctively dramatized her every surrounding, and amazed the luxurious Roman world with her calculatedly lavish display of Egypt's incredible wealth. Thus in this production, the photographic keynote was richness, and in every scene—even the most dramatic—the lighting was kept richly brilliant, to keep the audience subtly aware of the splendor of the settings and costumes Similarly, Cleopatra's entertainments of Caesar and Antony were lit and photographed primarily as sensuous spectacles, the high-lights of her exhibitionistic nature

I have photographed many of Ernst Lubitsch's sparkling comedy-romances, and more than a few similar stories directed by other Directors Few, if any, Directors can impart to action and dialog the peculiarly brittle brilliance which characterizes Lubitsch's work, and where one might stress the romantic phases, requiring much softer lighting and photographic treatment, and another might play everything for broader comedy, requiring more conventional, highly-keyed lighting, Lubitsch's own style demands an equally distinctive, scintillating bril-

FRANK C. ZUCKER J. BURGI CONTNER

MOTION PICTURE CAMERA SUPPLY, Inc.

LARGEST STOCK OF NEW AND USED PROFESSIONAL EQUIPMENT IN THE EAST.

We have for sale: Mitchell, Bell & Howell, Akeley, and DeBrie Cameras and Equipment—new, used and rebuilt.

Lenses, Motors, Tripods, Parts and Accessories and Laboratory Equipment

We only sell equipment that we can guarantee.

Phone write, wire or cable for quotations

Eastern Representatives
MITCHELL CAMERA CORPORATION
HARRISON FILTERS
FEARLESS PRODUCTS

723 SEVENTH AVENUE
NEW YORK CITY

Telephone BRyant 9-7755 Cable Address: Cinecamera

lionce in photography and lighting which is rarely applicable elsewhere

About the time thot this oppears in print, I expect to begin photographing Cecil De Mille's "The Crusades" While like most of De Mille's pictures, this will naturally stress the spectacular element, the interest (photographic as well as dromatic) centers mainly on two outstonding men—Richard of England ond Salodin, the Sarocen This hos o very impartont beoring on the photagrophic treatment of the film, especiolly upon the comera-angles ond the lighting Through my study of the script, ond my doily conferences with Mr De Mille, the Art-Directors, Costumers ond others, I am corefully building up o mentol imoge of the picture—scene by scene—os I wont it to reoch the screen I om trying to visuolize every angle, every phose of lighting, so that when I actually film eoch scene, I will have o definite, mentol plon of the technicol steps that must be followed so that the lighting will not only be in tune with the dramotic mood ond tempo of the octian, but will bring out the fundamentol troits of each chorocter.

The two principol chorocters ore in every woy of heroic proportians Richard the Lion-Hearted, King of England and Duke of Normandy, characterizes the epitome of European Chivolry of the Middle Ages Salodin, Sulton of Egypt, represents all thot was Knightly in the more highly cultured Sarocenic notion Both characters represent the flower of hardy, virile monhoad, ond tower obove their fellows in body ond in chorocter This gives on unusual opportunity for psychologico - dromatic cinematography Strength ond virility must predominate in the lighting of these men, who should be shown in strong relief ogainst the pictoriol, but less commanding background of the period ond of their followers To this end, I hope to depart from the conventional lighting technique, instead of ovoiding contrasts and strong shadows, for instonce, I plon to heighten them and to use them to express visuolly the strength of the two men Using os little os possible of the conventionol flat front-lightings ond outlining back-light, I plan to simplify my personal lightings, throwing features into strong relief, modelled by heavy shodows thot emphasize the note of ruggedness

To this end, I expect to use very little diffusion, either in the camera or on the lights, and instead of corefully eliminoting oll the resulting shadows under cheek-bones, noses ond chins, I plan to foster them, using them for dromatic effect Wherever possible, I intend to enhance the effect of towering physical strength, so that these men tower physicolly os well os dromaticolly obove the other players One scene in particular creates an especiolly strong mentol picture in my mind the scene where the two meet for a porley, surrounded by their oides As I visualize the scene, the two men stond together in the center of the picture, strongly, baldly illuminoted, ond towering obove their men, who ore grouped behind them in o semicircle, partly obscured in shadow The strength of the chorocters of Richard and Salodin con be expressed quite os much through the lighting os through diolog or octian

On the other hand, the women in the story demond the softest, most delicate lighting possible to fittingly express the Medieval ideal of womanhood The "emoncipoted womon" of todoy was nearly ten centuries in the future, and the twelfth century Chivolric concept of womonhood was os of something frogile, ethereolly lovely, almost too wonderful for the raugh men of the period to even touch This concept con be carried aut in the lighting soft, delicote lighting, possibly higher keyed ond ottuned to o greoter degree of photographic diffusion The contrast between the virile, olmost harsh photagrophic rendition of the men, and the delicate, pictoriol presentotion of the women should go o long way to estoblish in the oudience-mind this important dromatic controst

All of these concepts can be carried out in the personal lighting—the light-

High Fidelity Recording Galvanometer

(variable area system type)

to replace

Glow Lamps

FREQUENCY RANGE

0 to 10,000 Cycles



Patent Pending

This galvanometer and optical system may be readily installed in any recorder or camera now equipped with a glow lamp. It eliminates film developing difficulties, increases recorded frequency range, reduces operating costs and simplifies operation. Each unit is supplied with individual frequency calibration and is unconditionally guaranteed, regardless of footage recorded, to operate efficiently and satisfactorily for one year. Price, complete, $350 in U. S. A.

Literature and thorough technical description sent upon request.

The Berndt & Maurer Corp.

(Successor to Eric M. Berndt)

112 East 73rd Street New York City

Technical Details

All optical parts permanently adjusted in sealed tube Requires 6-volt battery for exciter lamp and field. Signal winding operates from 5 ohms or any standard line impedance up to 500 ohms Power required to drive is ¼ watt. Line image ½ mil by 70 mils, focused by micrometer screw with rigid lock Overall dimension, length 7½ inches, diameter of tube 1½ inch Image 5/16 inch from objective. We will mount it to any recorder or camera equipped with sound gate for slight additional charge.

1515 Cahuenga Blvd ,
Hollywood, Calif
Phone GLadstone 2404

ing of the players—while, like a musical undertone, the lighting of the settings synchronizes with the dramatic tempo of the action Where the action moves at a dramatically swift pace, the set-lighting can be of a relatively high key, where it grows melodramatic, there can be greater brilliance in the general lighting Where the action moves at a slower tempo, the lighting can strike a lower key Moreover, the spirit of the period can likewise find much expression in the lighting The buildings of the time were built for defense, rather than comfort, accordingly, the only illumination within them was from torches and candles, aided, in the daylight hours, by thin shafts of sunlight filtering in through tall, narrow windows and loop-holes To be historically correct, the lighting of such sets will have to reproduce, in some measure this known condition—and the photographic effects so produced will convey a perfect visual impression of the rough hardihood of the age With this background for the light-treatment of the players, there is an unusual opportunity for true dramatic cinematography and lighting

THE DIN-SCALE

Continued from Page 11

point on the curve is dependent upon the absolute light intensity, and therefore upon the light source by which it is read and upon the amount of the fog density (See the range indicated in Fig 1 by Schoeffur) 3. The primary light energy (intensity x time) employed is accurately constant, since a definite quantity (2 mg) of Mg-ribbon is burned

Finally it must be emphasized that this kind of evaluation of the speed is not good in practice In picture photography it is not so very essential to know what exposure is required to produce a just visible impression on the emulsion as, the much more essential quantity, what exposure produces a good image For the evaluation of speed according to the Hurter and Driffield system, a tangent to the density curve abtained from the exposed sensitometric strip is constructed For the determination of the H and D sensitivity number, the number 34 is divided by the light energy measured in m c s corresponding to the point at which the tangent crosses the abscissa Apart from the consideration that this method of speed determination is very bothersome on account of the necessity of constructing the entire density curve, the value obtained does not correspond to that which in practice corresponds to sensitivity So much trouble has arisen from the sensitometric systems spoken of, that it was resolved, in Germany, to produce a new method The problem was to find a system of sensitometry capable of exact reproducibility of speed number, one which designated the sensitivity of a photographic emulsion in a useful manner for practice, the system to be adopted for perhaps three years by the German Society for Photographic Research and executed by one of its committees on sensitometry The numerical value necessary for practical work has been worked out in detail in the laboratories of the Scientific Photographic Institute of the Technical High School of Dresden, the I G Farbenindustrie A.-G (Agfa), and the Zeiss Ikon A.-G also with the support of the Perutz G m b H A description of this work is to be found in an article by R Luther in the Proceedings of the VIII International Congress for Scientific and Applied Photography, 1931, in Dresden For on account of the

Hollywood
MOTION PICTURE EQUIPMENT CO. LTD.
645 NORTH MARTEL AVE. CABLE ADDRESS ARTREEVES
HOLLYWOOD, CALIFORNIA, U.S.A.



TRUEBALL
TRIPOD HEADS
OF SPECIAL ALLOY
LIGHTER WEIGHT

The Same Efficient Head
For follow shots, known for their smoothness of operation and equal tension on all movements
Unaffected by temperature

Model B Professional $300.00
For Bell & Howell and Mitchell Cameras and their respective Tripod With the ORIGINAL instant release telescopic handle.



Model A for Amateur motion picture cameras Attaches to any standard STILL Tripod, $12.00.

Trueball tripod heads are unexcelled for simplicity, accuracy and speed of operation

The Hoefner four-inch Iris and Sunshade combination is also a superior product.

FRED HOEFNER
GLadstone 0243
5319 Santa Monica Boulevard
LOS ANGELES, CALIF.

details, the reader is referred to this article From this point forward this new method of speed determination shall be considered with reference to the formerly outlined three simplifications

1 The light source used possesses approximately the same spectral distribution as sunlight It is obtained by means of a vertical filament tungsten vacuum lamp at a temperature of 2360° Abs in combination with a liquid Davis and Gibson filter The energy distribution of this light source in combination with this filter is compared with the energy distribution of the sunlight measured by Abbot.

2. The exposure time is constant and amounts to 0 050 sec , the light intensity is graduated by a gray step wedge in contact with the emulsion to be tested The step wedge has 30 steps, each 4 mm wide, which carry numbers 1-30 The first step (No 1) has the density 0 10, the second a density 0 20, etc , the last step (No 30) a density 3 0.

The density difference between each third step amounts to 0 3, the ratio of the transparency of the first to the fourth step, the second to the fifth step, the fourth to the seventh step, etc , has the value 2 The apparatus (Zeiss Ikon) which is employed for making the exposures has been described by Gothel and Seifert and is shown in Fig 3

3 The sensitivity is characterized by that energy for square cm of emulsion surface, which is required to produce a density of 0 1 above fog For the determination of this energy, it is not necessary to plot the density curve as in the case of the Hurter and Driffield method of evaluation, instead, one proceeds by laying a comparison strip of density 0 1 on the unexposed part of the sensitometric strip (image of the gray step wedge) and places it optically adjacent to the density scale The number of the step which has the same density as the fog plus the comparison density, characterizes the sensitivity and gives the DIN-Speed of the photographic emulsion considered Bringing the two densities optically adjacent may be accomplished with the help of a biprism The higher the number read, the higher the sensitivity of the emulsion and indeed a jump of three step numbers designates a rise by a factor of 2 in sensitivity The choice of the density 0 1 above fog has various bases A specification of sensitivity based on this value of density has regard for the rendering of shadow detail, which is absolutely necessary for the attainment of pleas-


Everything Photographic
for Professional and Amateur
New and Used, bought, sold, rented and repaired Designers and manufacturers of H C E Combination lens shade and filter-holder for any size lens
Hollywood Camera Exchange
1600 Cahuenga Blvd , Hollywood
Tel HO 3651
Cable Address HOcamex
Open 8 a m to 10 p m



The B & H
Production Printer
a money-saving money-making investment

Most laboratory operators know where the leaks are, where waste and inefficiency conquer profits. Bell & Howell has produced a fully automatic printer that will not only stop waste but producing prints of finest quality in both pictures and sound, will save its cost in a surprisingly short time. The wastage from mislights, out-of-synchronism, and time consumed in threading and cleaning is eliminated. The saving is sufficiently large to liquidate the investment rapidly. In laboratory service, these printers are regularly run continuously on a 24-hours per day schedule. Available by lease or purchase. Write for complete information

BELL & HOWELL COMPANY
1848 Larchmont Ave., Chicago; 11 West 42nd St , New York; 716 North La Brea Ave., Hollywood, 320 Regent St., London (B & H Co., Ltd.) Estabi'd 1907.

ROY DAVIDGE
FILM
LABORATORIES

Negative Developing
and Daily Print
Exclusively

6701 SANTA MONICA BLVD.
GRonite 3108

Scheibe's FILTERS
In World-Wide Use
Produce Moonlight and Night
Effects in Daytime Scenes-
Diffused Focus and effects
With any Camera - In any Climate
George H. Scheibe
ORIGINATOR OF EFFECT FILTERS
1027 WEST 75TH ST LOS ANGELES, CAL.

ASTRO F 1.8
F 2.6
LENSES

for sale by
Mitchell Camera Corporation
665 North Robertson Blvd.
West Hollywood, California

ing pictures, while a good rendering of the mean tones and high lights can be obtained through proper choice of the printing materials In addition, extensive research, which has been carried out, especially in Dresden, shows that the differences in sensitivity of the emulsions which are available for practical photography can be quantitatively represented by the DIN-scale A very important advantage of the method outlined consists in the fact that by this method the eye is not employed as an "absolute instrument" for the observation of a threshold value, but as a "null instrument" in which it has the task merely of observing the equality between densities Hereby individual differences should be largely eliminated

In contrast to all former systems of sensitometry, the method of development of the sensitometric strip is here accurately specified The developer is sulphite metol-hydrochinon developer and optimal development is to be given, i.e development for such a time that the highest possible DIN-number is obtained However, the density of the fog is not to be higher than 0 4 in case it is not specified under the DIN-Speed by the factory

The sensitivity of a photographic emulsion can be accurately determined to ± DIN-number. In order to furnish latitude for a small loss of sensitivity of an emulsion during storage, a tolerance of 3 DIN-steps has been established, i.e for a later test it is permitted that the sensitivity be (at the most) 3 steps-DIN lower than it was given by the factory An arbitrory sensitivity change (to one-half) is insignificant in comparison with the enormous exposure latitude of many modern photographic emulsions

The problem of DIN-speed, as well as a trustworthy sensitivity designated for photographic emulsions, has long been desired This must be seen as a real and, for the practical photographer, very delightful aovancement

PHOTOGRAPHY OF THE MONTH

Continued from Page 10

'NIGHT LIFE OF THE GODS" (Universal)

John Mescall, A.S.C.: Directing Cinematographer

Hollywood Reporter (December 7, 1934) "The photography is fair"

Daily Variety (December 7, 1934) "Photography of John Mescall is excellent, particularly the process footage of the transformations"

"MYSTERY WOMAN" (Fox)

Ernest Palmer, A.S.C.: Directing Cinematographer

Hollywood Reporter (December 7, 1934) "Ernest Palmer's photography is at all times interesting"

Daily Variety (December 7, 1934) "Photography is excellent, particularly night shots at sea"

"LITTLE MEN" (Mascot)

Ernest Miller, A.S.C.: Directing Cinematographer

Daily Variety (December 7, 1934) "Photography by Ernie Miller and William Nobles is excellent"

"BIOGRAPHY OF A BACHELOR GIRL" (M-G-M)

James Wong Howe, A.S.C.: Directing Cinematographer

Hollywood Reporter (December 15, 1934) "And James Wong Howe succeeds in making things look their best with his photography"

Daily Variety (December 15, 1934) "Photography of James Wong Howe is above par, particularly his exteriors"

CRONJAGER PASSES

Jules Cronjager, 62, veteran cinematographer, died at his home Christmas night following a heart attack after being ill for several weeks

Cronjager had been a cameraman for 25 years He is credited with some of the big productions of the industry during the silent days He is survived by his widow and a brother Henry Edward Cronjager, A S C, of the RKO Studio, is his nephew.

MAX FACTOR'S
Satin Smooth MAKE-UP
Easy to Apply - - - - - Easy to Remove
Stays on All Day - - - Photographically Correct
MAX FACTOR'S MAKE-UP STUDIO • HOLLYWOOD

1935

Prosperity
Health
Happiness

●

J. E. BRULATOUR, Inc.

EASTMAN FILMS

Here's the New FILMO 16 mm. Projector

that does a 35 mm. job

FILMO Model 130 Auditorium Projector 1000-Watt

SALIENT FEATURES:

1000-watt lamp—the most powerful light source ever used in a 16 mm. projector. Variable voltage resistance unit and voltmeter give precise control of lamp voltage and reduced illumination when desired.

New optical system—results in an illumination increase considerably greater than that attributable to the increase in lamp wattage.

Fast Cooke 2-inch F 1.65 lens, instantly interchangeable with others, from 0.64-inch to 4-inch, to obtain any desired picture size at any projection distance.

1600-foot film capacity—a one-hour show without a stop.

Low center of gravity—no accidental upsetting.

Film take-up by a separate motor which also provides power for rapid, automatic film rewinding.

Adequate cooling, by two fans and finned lamphouse, to keep the lamp at the proper temperature for economical use.

Film conditioning, by travel through a channel where the film is cooled and humidified.

Two-way tilt, for high and low projector placements, simply by turning a knob.

Other features. Manual framer, pilot light, error-proof interlocking controls, dark silver grey crinkle-baked enamel finish with black and nickel fittings.

Basic Filmo film movement mechanism and traditional Filmo perfection of design and construction.

Price, $385. Case, $27.50.



Filmo 129 Projector—750-Watt

Two New 750-Watt Filmos with 1600-foot capacity

The new Filmos 129-A and 129-B have streamlined bases, low center of gravity, and 1600-foot film capacity. They are supplied with 750-watt lamps, but take lower-powered lamps when less light is needed. Their standard 2-inch lenses are instantly interchangeable with others, from 0.64-inch to 4-inch, to meet varying requirements of picture size and length of throw. Filmo 129-A, with 750-watt line voltage lamp and carrying case, $185. Filmo 129-B, with variable resistance, voltmeter, and case, $210. Bell & Howell Co., 1848 Larchmont Ave., Chicago, Ill. New York, Hollywood, London (B & H Co., Ltd.) *Established 1907.*

BELL & HOWELL

FILMO

Personal Movie Cameras and Projectors

PROFESSIONAL RESULTS WITH AMATEUR

AMATEUR MOVIES

January
1935

Price 25c

this issue

Equipment Prize Winners
Talk an Lenses
Reversing Film at Hame
Gadget Winner far Manth
. . and other features

AGFA 16 MM. *Superpan Reversible in the black and green box.*

INSIST ON AGFA SUPERPAN

For Your Choice Indoor Scenes

AGFA 16 MM. FILMS

AGFA FINE-GRAIN PLENACHROME
100-foot rolls $4.50
50-foot rolls 2.75
Including processing and return postage.

AGFA PANCHROMATIC REVERSIBLE
100-foot rolls $6.00
50-foot rolls 3.25
Including processing and return postage.

AGFA FINE-GRAIN SUPERPAN REVERSIBLE
100-foot rolls $7.50
50-foot rolls 4.00
Including processing and return postage

AGFA FINE-GRAIN PANCHROMATIC NEGATIVE
100-foot rolls $3.50
Developing not included.
200-foot and 400-foot rolls (laboratory packing) available.

• To get indoor scenes that can be projected to large size with clear, sharp detail, you need the speed and fine grain of Agfa 16 MM. Superpan Reversible.

The fine-grain emulsion of Agfa Superpan Reversible has built an enviable reputation among filmers who strive for large screen projection from 16 MM. film without noticeable grain.

The high speed of Superpan—twice as fast as regular Pan in daylight and three times as fast under artificial light—is combined with emulsion qualities which assure depth, brilliance and detail in the projected image.

Superpan is sensitive to all colors including red, giving full range of tone values, and the wide latitude reduces possible exposure errors.

For the finest results with indoor scenes, insist on Agfa 16 MM. Fine-Grain Superpan Reversible Film.

Made in America by

AGFA ANSCO CORPORATION
BINGHAMTON NEW YORK

NRA CODE

Boston New York City, Cincinnati, Chicago, Kansas City, San Francisco, Los Angeles • Agfa Ansco Ltd., 204 King St. East, Toronto, Ont.

Agfa

FOR BEST RESULTS USE BEST MATERIALS

AMATEUR MOVIE SECTION

Contents . . .

EQUIPMENT Prize Winners. 24

NON-SYNC Setup for Silent Pictures
by Arthur H Smith 25

TALK on Wide Angle Lenses
by Wm J Groce 26

FORMULA for Reversing Film 28

ADAPTING Professional Lighting
by Frank Good, A S C 29

WHEELS of Industry 30

HERE'S How
by A S C Members 32

TRICKS and Gadgets Winners 34

PROFESSIONAL Criticism of the Amateur picture is a part of the service offered by the AMERICAN CINEMATOGRAPHER. Many are not aware of this. Hundreds of pictures have been reviewed this past year by members of the American Society of Cinematographers for the Amateur.

Next Month . . .

● We will give you the details of the 1935 Amateur Movie competition There will be a little change in the date and a little change in the classifications. Everything will be simplified more

● There will be articles pertinent to problems you encounter frequently We will tell you something more about animated cartooning and how sound is synchronized with the action

Equipment Prizes Awarded

DURING the past month the judging committee of the American Cinematographer 1934 Amateur Movie Makers Contest completed its work and designated the winners of the equipment prizes and those who were to receive Honorable Mention

The prize given by Eastman was awarded John E Earl for his picture "The Traveler" This picture was selected because it wos felt by the committee that it not only was a good travel subject, but also one that had as its central theme the family of the producer

The Bell & Howell prizes according to the rules went to the winners of prizes in the cash awards to those who used Bell & Howell cameras

The Victor Animotograph Camera was given outside of the regular awards In every case where this was possible the committee attempted to separate the equipment awards from the cash awards "Footsteps" would easily hove won in one of the classifications, but the picture was of a calibre that the committee believed should receive a higher award.

The Agfa contributions were also rated in the same way If the picture was made on Agfa film it was first put in the class to be judged for the Agfa prize as that prize was greater than the cash prize except in the case of the first winner Under this arrangement Mr Nixon of Cleveland, Ohio, was given the prize of the Super Pan film for his fine picture "Christmas" This combined fine photography, both interior and exterior, with a splendid record of the holidays In view of the fact that the Calvin Co award came under this same classification Mr Nixon also won that prize

The second prize of the Agfo Ansco Corp went to Arthur Wolff of Chicago for his film "All for Beauty," a documentary picture

The Harrison & Harrison prize was awarded to Chas E Coles ond Robert Coles of New York City for their picture "Rainbow Trail" Last year these two gentlemen won the second prize for photography

The Craig Splicer and Rewind went to W McFarlane of Rochester for his picture "Two Tramps Abroad," a splendid record of a honeymoon trip cleverly edited ond titled

The Sunny Schick prize of one Model M S A Electraphat went to J J Urban of Ft Atkinson, Wis, for his picture "Our Family"

In addition to these prizes the committee felt that the following were highly deserving of Honorable Mention

Allan F Seaver, New Bedford, Mass, for his picture "New York City"

Dr Harold F Kaufman, San Francisco, Calif, for his picture "Around the Clock with Muriel"

C J Kostich, Long Island City, N Y, for his picture "Peasants"

Dr S H McAfee, New Orleans, La, for his dental picture.

Delmir DeCaralt of Barcelona, Spain, for his picture "Memmartiga"

Claude W A Cadarette, Los Angeles, Calif, for his picture "California Missions," an 8mm subject

Cinema Club of San Francisco for their picture "Shades of Bacchus"

Joyn F Criswell of Los Angeles for his picture "America Thru the Ages"

M P Gamber, Grand Rapids, Mich, for his 8mm picture "Hooked."

Equipment Winners

Eastman Model K-75 Projector, Value $235.00, to John E. Earl, for his picture "The Traveler."

BELL & HOWELL, Merchandise to the value of $125.00 to Van Dee Sickler for his picture "Mischief."

Bell & Howell, Merchandise to the value of $75.00 to H. Demarest of Hackensack, N. J., for his picture "Story of Water."

Victor Animatograph Corp, Model 5, 16mm Camera with f2.9 lens, value $175.00, to J. R. Coming, St. Louis, Mo., for his picture "Footsteps."

Harrison & Harrison Universal Filter Holder and set of Multi Filters, value $14.00, to Chas. H. Coles and Robert Coles. New York City, for "Rainbow Trail."

Craig Movie Supply Co., Senior Rewind and Splicer, value $19.50, to John W. McFarlane, Rochester, N. Y., for 'Two Tramps Abroad."

Agfa Ansco Corp., 12 one-hundred-foot rolls Super Pan Reversible 16mm film, value $94.00, to C. E. Nixon, Cleveland, Ohio, for "Christmas."

Agfa Ansco Corp, 12 one-hundred-foot rolls Plenechrome Reversible Film, value $54.00, to Arthur Wolff, Chicago, Ill., for his picture "All for Beauty."

The Calvin Co., Complete Set of Tailor Made Titles, value $50.00, to C. E. Nixon, Cleveland, Ohio, for "Christmas."

Sunny Schick, one Model M.S.A. Electrophat, value $17.50, to J. J. Urban, Ft. Atkinson, Wis., for "Our Family."

Continued on Page 35

Non-Sync Setup for Silent Pictures

by
Arthur H. Smith

The duel turntable case, showing the input A. C., the two output jacks and patching cords The two off-on switches two control switches and the fader The pickups and motor turntables are mounted on the top



Wiring Diagram for Duel Turntable

THE following describes a "non-sync" setup which is portable and which incorporates a monitoring circuit and a feature whereby sound effects may be simultaneous with the background music This arrangement is built into two cases for ease in transporting and is very convenient for temporary setups

Two plywood suitcases about 24"x15" are used to house the complete setup The first case contains two 33 1/3-78 r p m electric turntables, two electric pickups and the associated wiring The second case contains the amplifier This amplifier is really two amplifiers The first, or main amplifier, is for the sound and the second is the monitor amplifier

The operator, at times, wishes to pick out sections of a record for accompaniment with the picture In this system I have provided a means whereby the operator may monitor on the incoming pickup with a pair of headphones and find the exact spot for setting his needle For instance the action might be slow and light, then a fadeout and a quick fadein on fast exciting action One record may have fast exciting music about halfway in it Yet, the operator will not wish to play the first part of this record as a better record may be on hand for the slow action preceding the excitement So, he plays the slow music, sets the incoming pickup about where he wishes to pick up the hurry-hurry and listens for the start and then fades over to catch the opening notes

Two outlet jacks and a 11°V, A C input are mounted on one end of the turntable case One output jack is connected by means of a patching cord to the input of the main amplifier and the other output jack is connected by means of a second patching cord to the monitor amplifier. The input for the 11°V A C is on ordinary outlet receptacle and a special cord is made up with two male plugs for connecting to a power outlet Each motor has its own on-off switch Each pickup comes with a volume control as part of the pickup assembled in one unit. Therefore, no volume controls need be mounted on the case However, for each pickup circuit there is a four-pole three-position switch For this switching arrangement a Kellogg anti-capacity switch may be used, but, a slight adjustment will have to be made on the inner contacts These must be bent so as to contact with the swing arms when the key is in the center position The diagram of the turntable case shows such a position on the right hand pickup while the left hand pickup in the diagram has the key in the down position

Here is an explanation of operation

The amplifier and speaker are set up, and the duel turntable case is connected with the patching cords With the key associated with its particular pickup in the down position that pickup is on the main amplifier channel and will feed music into said channel provided the fader is turned to that pickup With the key in the center position the pickup is on the monitor channel and can be heard in the headphones With the key operated up it throws the pickup in parallel with the playing pickup This is used in the following case The action on the screen shows a train thundering along a track Background music is being played Now, as special records may be secured for almost any type of sound we will say a record has been secured for a train whistle That is put on the vacant turntable and the motor started Now at the critical moment the key is thrown up and through the background music will come the "toot-toot" of the train whistle

The amplifier is built into one chassis It is mounted in the cover of the second case and the loud speaker is mounted in the base It will be necessary to remove the hinges and replace them with clasps similar to those on the front of the suitcase These may be obtained in a suitcase repair shop Then, the speaker may be detached and placed near the screen

The main amplifier consists of 2-56's into 47's in push-pull and the 80 rectifier The monitor amplifier is a single 56 into a single 45 with its 80 tube The monitor amplifier also supplies field to the dynamic speaker Of course, variations can be used The main thing is to supply two amplifier channels so that one amplifier channel is available for the sound while a second channel is available for monitoring If an A C speaker is used then of course it is unnecessary to supply field from the monitor amplifier

If it is desired a microphone may be fed into the input of the amplifier for explanations during the picture A mike transformer and battery is all that is necessary and this may be built into a small box which will fit into the amplifier-speaker case when transporting

Music with pictures improves their entertainment value about 50%





Figure 9. By combining a dispersing lens with a converging lens, the telephoto effect of enlarging the image is obtained without correspondingly longer mounting length and large diameter required by a normal long-focus lens.

Let's Talk

IN THE first two articles of this series in which we have become better acquainted with the whys and wherefores of our camera lenses, the rudimentary optical faults of the single common lens have been discussed with the idea of realizing more fully why the lens of our cameras is so important to the quality of our picture work. And, altho intricate mathematics was purposely avoided, the discussion at least, I trust, has made us aware of the problems confronting lens designers and manufacturers, and perhaps their ceaseless efforts to supply us movie fans with better and better lens equipment have increased our respect for their talents.

The third article of the series (which appeared in last month's AMERICAN CINEMATOGRGAPHER) was an attempt to learn, in at least cursory fashion, the progress which has been made in modern lenses, with illustrations of the general types of modern anastigmats. In order to correct for as many optical faults as possible simultaneously, groups of lens elements were combined in proper manner, to be followed by later advances which increased the speed of lenses without increasing the aberrations by the simple expedient of selecting glasses and shapes which minimized the number of lens elements and thus increased the optical efficiency.

This month we shall discuss in more particular fashion two special members of the lens family—the wide angle and the telephoto lens.

When the gasoline-powered conveyance was first marketed, it was offered in only one body style, the two-seat open model. It was the plaything of the rich and nothing more. With the spread over the country of such a convenient mode of transportation, people not-so-rich visualized the motor car as having possibilities in other directions than the mere Sunday-promenading of the first models. The salesman who seldom had a passenger found a roadster or single-seat model more easily maneuvered because of its smaller size. Families in wet or cold weather began to demand more comfort in their transportation. Trucking companies realized that different models of the motor car might be built to more economically and more quickly carry heavy burdens of freight than the horse-drawn vehicle could accommodate. In short, the more general and widespread the knowledge of the advantages of motor transportation, the more widely varied became the models of the motor car.

The amateur motion camera and its lens are paralleling the history of the motor car in that as more and more enthusiasts are recruited into the field, the more widely varied are the models of cameras and lenses which manufacturers offer. Up to a certain point in this evolution, there is a great deal of healthy competition, but beyond a certain saturation point, there will be the reverse swing to simplicity.

Just at present, there are so many different focal length lenses on the market that there is actually sales resistance to all cine amateur equipment. Perhaps I should modify or qualify that statement by the explanation that because so little is told of the reasons for the existence of all these lenses, there is a definite reaction against getting into the game because "it's a rich man's game."

But we don't shy away from owning a modest automobile just because the rich man's equipage consists of a town car, a country car, and a few incidental pieces of motoring equipment do we? We might have a longing for a better car, but you can bet your last bottle of film cement that we feel that should we ever be fortunate enough to be financially able to possess more motor equipment, we'll know exactly what we need.

So it is with lens equipment for our amateur movie camera. Until we know more about our possible future needs, we start out with a normal focal length lens, a good, safe choice. But as we aren't ever satisfied with our past and present achievements, it will be a good idea to store away knowledge of what we might need in the future.

And that brings us to wide-angle lenses and telephotos. What are they? Why are they? What good can they do us? If we approach a case full of lenses with itching fingers and loose-stringed pocketbook, let's ask three questions of every lens the dealer shows us, and then blame no one but ourselves if the wrong choice is made in auxiliary lens equipment.

What is a wide-angle lens? Why is it offered to us? What good would a wide-angle lens in our camera be to better filming?

In the first place, a wide-angle lens is a lens which gathers optical impressions for our film in a wider sweep than does our normal lens. A wide-angle lens is offered to us because in interior filming so many amateurs have complained of the regular lens being too "narrow-eyed" to include enough scene taken in our small-roomed modern homes and apartments. If we have a wide-angle lens in our equipment, we can film family movies indoors and

About Lenses Wide-Angles and Telephotos

by
Wm J. Grace

Not to be reproduced in any other publication without the permiss on of the author

get plenty of odjocent scenery to estoblish the foct that it is reolly a room and not just o two-wolled ortificiol movie set.

The diogonol of o frome of 16mm film is about ½" With o 1" lens (sometimes colled o 25mm lens), then, the included angle is about 26½°. If you're mothemotícolly inclined, the ongle is the onti-ton of half the diogonol divided by the focol length Consequently, o 15mm wide-angle lens will cover about 33° on the diogonol (ogain, the onti-tan of holf the diogonol divided by the focol length). It isn't difticult mothematics to prove thot 33° is about 25% wider ongle thon 26½°, ond it likewise isn't difficult for the loymon to realize thot o picture made with o 15mm wide-ongle lens will include 25% more scenery all oround thon the normol 1" lens

Why oren't still wider-angle lenses on the morket? Simply becouse the need hosn't developed to such proportions os to warront poying the solory of a high-priced lens designer or investing in opticol grinding equipment necessory to such short focol lengths When the need becomes greot enough, we shall hove wider-ongle lenses, hove no fear. True, the focal length will be so short that the lens moy practicolly ride on the film, but if we wont them, lens makers will come thru in fine style, never feor!

As an example of whot hos actuolly been done in the woy of wide-ongle lenses, the Goerz Opticol Co developed o few yeors ogo a lens which was onostigmoticolly flattened over o field of obout 135°! But the Hypergon, os it wos trode-named, wos not for the 16mm enthusiost, for [illegible]vercome the uneven illumination of the film surfoce (a fault common to wide-ongle lenses, but, of course, corrected in commerciol lenses) by the complicated expedient of exposing with the film for obout 1/6 total time with the lens alone, and the remoining 5/6 wos exposed with a stor-shaped ouxiliory field stop, which wos spun in front of the lens by an oir blost, swung before the lens Imogine doing this 16 times per second! One would hove to be o bit ogile, os it were, would one not!

You wide-ongle fons who hove been crying for "wider, wider, **wider**" angles to your lenses, digest the obove description of a reolly **wide**-angle lens, and be content with whot you hove.

And now to the other side of the normol lens—the telephoto lens Whot is a telephoto lens? Why is it offered to us? What improvement would come to our filming thru the use of telephoto lenses?





Figure 8 The wide-angle lens "takes in" a wider angle of view than the normal lens. Its chief use is in filming interiors where the camera cannot be backed far enough away from the scene to include the proper amount of surroundings.

Well, o telephoto lens is o hybrid lens, in the first ploce It's a long focol length lens with o short focol length mounting tube It is existent only becouse we hove demonded thot even long focus lenses for our tiny omateur movie comeras must be in keeping with the physicol dimensions of our compact comeras Surely, they cost more than o regular lens would cost, because of the extra lens element in it It is an importont lens for us, tho, becouse it ollows us to film objects in a lorger size than if we hod to depend on the normal lens, from the same comero-object distance

If you are a still comero enthusiost as well os a movie bug, os most of us in 16 ond 8 are, you ore fomilior with the rother lorge backward ond forword travel of the lens of, soy, o 2¼"x3¼" Groflex hoving the normol 5½" lens Your own comera moy be smaller or lorger thon this and hove o correspondingly shorter or longer focus lens, but you do know that the lens on your still camera must travel on oppreciably longer distonce in moving from perfect focus far o close-up to sharp focus for o distant scene

As on example, the 5½" lens of my Graflex moves about 5" between the extremes of o closeup ond o distont object, while my 6" telephoto on my Bell & Howell only moves about 5/16" for the same odjustment Moreover, when racked out to shoot a closeup, the 5½" Graflex lens is about 10" or more oway from the film, while the 6" Cooke telephoto is only obout 4" oway

The short mounting of o telephoto lens not only is o boon to the omateur cinephotographer becouse of compoctness, but it does not unbolonce the camero os much os would o normol lens of the same focol length The longer the focal length of a smoll cine camero lens, the more highly is magnified ony slight movement of either the lens or the camero, ond if the borrel of the lens is kept short, as is possible with telephotos, there is less donger from lens movement to spoil the shot

Continued on Page 36

Formula for Reversing Films

Editor's Note. So many requests have reached us for a formula for reversing 16mm film that we are reprinting herewith the article as it was originally printed in the Cinematographic Annual Vol. 2.

THE making of direct positives, whether by the reversal-film process generally used by amateurs, or by converting an ordinary negative into a positive, consists in making a negative on a strip of film, developing it, and then printing that negative on the same strip and destroying the original negative chemically, but leaving the positive print to be developed, etc., in the usual way.

In 35mm use, where regular reversal film is not available, either negative or positive film may be used, but where the light permits, positive is preferable, as it gives snappier results, although it is not corrected for color-values. As positive stock is for slower than negative, it can only be used under the best light conditions, and always with a much wider diaphragm opening than would be used with negative. It is not recommended for interiors. In any case, the exposure must be rather full.

The apparatus needed is a SOLID drum of metal or wood, painted with a dead black photographic enamel which must be resistant to the action of photographic chemicals. A SKELETON-TYPE DRUM, WITH ONLY RIBS, CANNOT BE USED FOR REVERSAL PROCESSING.

Any high-contrast developer can be used. The following is a good formula:

HYDROQUINONE	1 ounce
Sodium Sulphite (dry)	11 ounces
Sodium Carbonate (dry)	7 ounces
Potassium Bromide	1 ounce
Water	1 gallon
Alcohol	1 pint

The alcohol may be omitted, but permits development at a higher temperature, giving greater contrast.

Development should be slow, by dim, red light, so as to give a snappy negative with pure whites and deep blacks. Be sure to develop fully.

Wash for five minutes or more, to remove all traces of developer.

At this stage, any swelling of the film should be taken up by tightening the film on the drum. Then the film should be exposed to a diffused, white light until the white portions of the film became visibly grayed.

The next step is to destroy the negative image by immersion in:

Water	1 gallon
Potassium Bichromate	1½ ounces
Nitric Acid	3 ounces

The film is immersed in this bath until the negative has entirely disappeared, and only the creamy white of the remaining, undeveloped silver bromide is visible. After this, the film must be thoroughly washed, and the final, positive image then developed in the usual manner. This may be done in the same solution in which the negative was developed, or in some softer-working solution.

After this development, the print is fixed and washed in the usual manner.

Another set of formulae, especially intended for substandard reversal emulsions, are recommended by Messrs. Pathe for use with their Pathex system.

The formula for the first development is:

Parophenylenediamine	150 grains
Sodium Sulphite (crystals)	1 ounce
Caustic Soda	150 grains
Potassium Bromide	60 grains
Phenosafranine (solution 1-1000)	160 minims
Water	35 ounces

If ANHYDROUS sulphite is used, only ½ ounce is needed. There are also several commercial desensitizers, such as "Desensol," etc., which can be readily substituted for the safranine solution required.

This developer must be used at temperatures between 60 and 65 degrees F.

The developer should be filtered before use. Remember, too, that the caustic soda is bad for the eyes, so do not splash the developer.

In developing reversal film, the film should look almost opaque when the development is finished, and the black portions of the negative should appear of almost equal density from either side of the film. The following table will be useful in timing the development:

If the First Signs of Image Appear in:	Develop for
Up to 20 seconds	5 to 8 minutes
30 "	10 "
40 "	12 "
1 minute	15 "
1¼ to 1½ minutes	20 to 25 "

Reversion is in this case carried out chemically, by use of the following reversion bath:

Potassium Permongonate	30 grains
Sulphuric Acid	170 minims
Water	35 ounces

The acid should be added last in a slow stream, stirring the while. Sodium Bisulphate (380 grains) may be substituted for the acid, but is not as effective.

In reversion the negative is dissolved away and the film takes on a red color. This normally takes from seven to ten minutes, but should in any case be continued until all of the black image is dissolved. If the amateur has both orange and red lights on his dark-room lamp, the red one may be removed after the film has been five minutes in this bath.

After reversion the film is washed until it becomes a clear yellow—usually about seven minutes. The remaining operations may be carried out in white lights.

The next step is bleaching, by the following formula:

Sodium Sulphite (crystals)	150 grains
Sulphuric Acid	35 minims
Water	35 ounces

Continued on Page 36

Adapting Professional Lighting to Amateur Movies

by

Frank Good, A. S. C.

THERE is no gainsaying the fact that the average amateur-movie interior is either too flat, or too excessively contrasty. The fault, in the first instance, is that a general flood of light (from one or more sources) is indiscriminately thrown on the set—with no accentuating shadows or high-lights. In the other case, the light is from a single source, as a rule, so placed as to "burn up" most of the high-lights, and leaving a lot of heavy, black shadows.

Now, how shall we correct this? In the first place, why not begin with a general illumination from two or three well-placed lamps, fitted with silk or tracing-cloth diffusers. This is good insurance against unpleasant shadows, but it won't, naturally, give you anything but a flat, well-illuminated picture. If we want character in it, we will have to build up our high-lights from this foundation.

This is a good start, but now, how about the high-lights and shadows that will give our set character? These can come from other units—not diffused—and placed here and there about the room where their beams will make little catch-lights on irregular wall-surfaces, curtains, orchids, and furniture. The various types of inexpensive Photoflood units are fine for this. The light-source in a Photoflood bulb is fairly small, and so the light is intense enough to give a strong beam, which will accentuate our high-lights nicely, and also cast interesting shadows. In addition, Photofloods placed in ordinary table or bridge lamps will add to the naturalness of the effect, putting more highly-illuminated splashes of light in the logical places.

Clearly, if we build our light up this way, we're likely to get so much more than merely enough illumination to make on exposure, that we'll have to stop down quite a bit. Well, why not? Stopping down will give us more depth of focus—and it will also allow us to control the effect we get, closing down will give a darker, more contrasty picture, while opening up will give us a lighter, softer one. The best guide, of course, is an accurate exposure-meter (preferably one of the photoelectric type) normally, follow its reading, but for effects, note the reading, and then modify your exposure to get your effect.

Now let's consider an actual example, and see what can be done under normal conditions. Take the room represented in the sketch—a living-room of average size. Our shot will be made with a 15mm lens, centering on a person seated in a chair, and including a corner of the room. (It is always better to show two of the walls of a room this way, rather than a single wall.) Beside our chair are a book-table, on one side, and a reading-lamp on the other. Now, let's begin to light our picture! What do we want first? Our foundation-light, the soft, general illumination, from which we can build up our high-lights. We will start with lamp "A"—a 500-watt photographic lamp, fitted with a diffuser. Placed as it is, it will give us a nice, soft, general illumination over the picture-area. Used alone, it would give us an even, general illumination sufficient for an exposure—but the picture would be flat and uninteresting. You could balance it, of course, with another, similar unit placed on the other side of the camera-line, and a bit closer to the subject. this would result in a fairly good, ordinary lighting on subject and background. But, if you're like most amateurs, with none too many lamps at your disposal, I think you could get a better lighting for your set with but a single front-light unit.

Now, what do we want next? Well, some high-lights along the folds of that curtain in the background would

Continued on Page 33



Above—How the Amateur can do it. Below—How the Professional does it: how Ernest Palmer, A.S.C., set the lights for a scene from "Cavalcade."

WHEELS OF INDUSTRY

Craig Moves

● Craig Movie Supply Company announce the removal of their offices on January 1st to 1053 S Olive St, Los Angeles, Calif

This is almost next door to the local Agfa offices The new and larger quarters were made necessary by the many new pieces of equipment and material that are being handled by this company In addition to home movie materials the Craig company is also handling still-picture equipment

Boulder Dam Films

● The Boulder Dam Service Bureau of Boulder City, Nev, announces six subjects available of this project Some are in 16mm and some in 35mm

In addition to film the company also has lantern slides of the building of this vast dam

The 16mm subjects range in length from 100 feet to 2,400 feet

Chenges Name

● Educational Projecto Film Co of Hollywood has changed the name to Camera Mart This company has also moved from its former location on Cahuenga to 1611 N Cahuenga Boulevard

Agfa Color for Rolleiflex

● According to an announcement from Burleigh Brooks, distributor of the Rolleiflex camera for America the new Agfa Color will be available for that camera about the first of January, 1935 Announcement would indicate that this process is developed to such a point that it is much faster and much easier to use

Single Exposure Device

● A new accessory for the Leica camera is announced by E Leitz, Inc The Single Exposure Film Holder is a thin metal device which holds a strip of standard 35-mm film of from two to three inches long This carrier slips into the regular Leica camera and makes possible the exposing of a single negative

To make single exposures in this manner, the camera is of course loaded and unloaded in a darkroom, and the device is intended primarily for testing purposes, which it serves admirably well

This single exposure apparatus is not to be confused with the "Oligo" Single Exposure Camera, which is a complete camera in itself The device is for use in any standard model Leica camera

Kodak Retina

● This tiny newcomer in the miniature field takes thirty-six pictures on a roll of film supplied in a daylight-loading

magazine Two emulsions are available Kodak "SS" Panchromatic Film (No SS135) and Kodak Panatomic Film (No F135) The actual picture size is 24x36 mm

Loaded as easily as a Brownie, Kodak Retina carries all of its controls within easy finger-tip range Two large knurled knobs facilitate the winding and rewinding of the film The film is always locked in position At a turn of the conveniently located film-release knob only enough film for the next exposure can be wound forward, when it again automatically locks This eliminates any chance of overlapping, resulting in wasted film Once set at the first exposure, the succeeding exposures, up to 36, are automatically shown on a dial In a split second the picture taker is ready for the next exposure This speed in operation is invaluable when and if it is necessary to take a series of pictures of moving subjects

The film is numbered from 1 to 36 and when developed the number of each picture appears on the margin of the Kodak Panatomic or "SS" Panchromatic Film loaded in the new Kodak film magazine This new feature enables the user to order prints and enlargements for his film strip by number

With eight speeds including 1/300 second, time and bulb action, the well-known Compur shutter is capable of handling almost any subject

The shutter versatility is matched by the speed of the f 3.5 anastigmat lens When the Retina is closed it affords complete protection to the lens

Two Kodak Portrait Attachments and three color filters are available The "A" portrait attachment, with distance set at "infinity," reduces the focal distance to 41 inches, "B" reduces it to 25 inches When the camera is focused at 3½ feet these distances are reduced to 21 inches and 16 inches, respectively

The three color filters are light yellow (N-1), medium yellow (N-2), and green (N-3), with filter factors under daylight of 1.6, 1.9 and 2.2 respectively

Filters and portrait attachments screw into the lens mount and are so compact that the camera can be shut with either —but not with both—in position Filter and portrait attachment may be used together when the camera is open

The retail price of the Kodak Retina is $52.50

New 16mm Film Reel

● Herman A DeVry Inc announce a new 1600-ft 16mm reel The rims and spokes of this reel are of spring steel bands, bending easily but instantly returning to their original alignment The spokes are riveted to the rims, but at the hub they slide under a steel band to allow for the molecular expansion which metal suffers when bent or subjected to any violent strain

Another innovation is a well in the top of the hub to hold the film in the reel when starting the rewind The film is laid over the well and pressed lightly with the finger, film perforations catch on prongs and hold the film securely until end of run

Continued on Page

Admittedly...the Pick of the 16mm. Field

CINÉ-KODAK SPECIAL



- Ground-glass focusing
- Variable shutter
- Back wind
- Masks
- Double lens turret
- Interchangeable film chambers
- Long-running spring motor
- One- and eight-frame cranks
- Variable speed
- Single-frame release
- Fades
- Dissolves
- Double exposures
- Slow motion
- Animation



. . . slipping mask into position between lens and film



FREE...A large-sized 16-page booklet detailing the advantages of this finest of 16 mm. motion picture cameras. Write to Eastman Kodak Company, Rochester, N. Y., for "Presenting Ciné-Kodak Special."

Only Eastman makes the Kodak

HERE'S HOW

by A. S. C. Members

HOW can I hyper-sensitize film for use in my miniature camera?
—A. R., Rangoon, India.

For those who wish to hyper-sensitize film for greater speed, the following process may be employed

The strongest form of commercial ammonia should be used This is 28% The bathing of the film must be done in total darkness and in a clean room free from dust A **clean** miniature film developing tank is suggested for convenience Use one part of ammonia to twenty-four parts of water and be sure that the solution is kept at 50 degrees F Pour the solution in the tank and agitate gently for one minute Care must be taken to prevent the formation of air bubbles on the film Transfer film to a bath of equal parts of water and grain alcohol This is to facilitate drying Dry quickly in front of an electric fan, being careful to avoid dust The film should be used as soon as possible

—Clarence Slifer, A.S.C.

WHAT developing formula would you suggest to secure maximum density with miniature camera negatives?
—A. R. C., New York City.

The D82 formula for maximum density development is as follows

Water (125 degrees F.)	24 ozs
Wood Alcohol	1½ ozs
Elon	200 grs
Sodium Sulphite (desiccated)	1¾ ozs
Hydroquinone	200 grs
Sodium Hydroxide	125 grs
Potassium Bromide	125 grs
Water to	32 ozs

Developing time is four to five minutes at 65 degrees F.

If the solution is diluted and the wood alcohol left out, it will lose its developing energy

—Clarence Slifer, A.S.C.

WHAT would you consider the slowest shutter speed with a hand-held camera?
—A. M., St. Louis, Mo.

While it was suggested that 1/20th second be considered as the slowest shutter speed that may be safely used with the hand-held camera, it was not meant to discourage you from using slower exposures They may be used, when it is the question of a fair picture or no picture at all With my model F Leica, I have made many satisfactory hand-held exposures up to one second in duration However, the greatest care must be exercised An extremely valuable aid for slow exposures is the Grace Beltipod (a unipod camera support that slips over the belt or overcoat button) Such a support facilitates the using of slower or longer focal length lenses for night photography Just imagine the exposure and photographic possibilities obtainable with an f2.0 lens and one second exposure

—C. W. D. Slifer, A.S.C.

IS IT possible to print 16mm negative on 35mm positive stock, that is, enlarge 16mm to 35mm? Would this procedure cause the grain to become coarse? Is there any fine grain developer that would overcome this difficulty?
—L. G., Chicago, Ill.

While it is physically possible to enlarge 16mm to 35mm it is not considered practicable because of the coarseness of the grain This has been done on several occasions when no other type of negative or print was available At the time of the Lindbergh kidnapping the prints of the Lindbergh baby shown in the newsreels were enlargements of 16-mm pictures made by the Colonel of his baby

The present newsreel shots of the Galapagos Island mystery showing some of the people who are down there are seemingly enlargements of 16mm It is a well-known fact that G. Allan Hancock, the scientist who is familiar with these islands and who has cruised them frequently, has taken many 16mm pictures of them and the people on them In recent news reels he is given credit for the pictures of the islands and the people on them It is possible that these pictures were also enlargements of 16-mm At least they have every evidence of being dupes or enlargements

—Ray Fernstrom, A.S.C.

SOMETIMES in close shots, I find that although I carefully frame my shots in the finder, on the screen the subjects often have the tops of their heads cut off. Why is this?
—W. L. D., Cambridge, Mass.

This is caused by what is known as parallax between the finder and the lens Obviously, your finder is on top of the camera, when you get close to your subject, the finder and the lens do not cover exactly the same field, due to the distance between the finder and lens Most modern cameras have an adjustment on the finder—usually a means of sliding the eyepiece up to alter the finder's angle of field—to compensate for this (If the finder is at the side of the camera, the error and adjustment are, of course, to the side.) If your camera has no such adjustment, the only thing to do is to remember whenever your subject is closer than ten feet from the camera, and sight through your finder allowing more than ample head-room at the top of your picture

—David Abel, A.S.C.

WHY is the film for the 8mm cameras furnished in the 16mm width and slit after exposure and development? Why isn't this film furnished us already split in the 8mm width?
—S. R. C., New York City.

According to tests made by the Eastman Company it was found that the furnishing of the film split in advance would not be so practical as furnishing it in 16mm length. If you have attempted to develop motion picture film in any lengths you know it will stretch It was found in testing film split into an 8mm width that the stretching of this film was greater than in the 16mm width so much so that it was inclined to come off the drying drums longer than before it was processed This would mean a lot of trouble in accurately-made projectors It might also keep the operator busy with the framing lever attempting to keep his picture in frame In my own experience I have found that this film will stretch a little even after it is processed because of its very narrowness The strain in the projector and in the rewinds is to pull this film, so the tendency would be to lengthen it

—Arthur Miller, A.S.C.

Adapting Professional Lighting to Amateur Movies

Continued from Page 29

relieve the flatness of that part of the view, so we'll place lamp "B" either on the bookcase to the left, or on a high stand near it Lamp "B" can be either another 500-watt unit (undiffused), or a Photoflood unit It will give us these background high-lights we want, and, if properly placed, it can also simulate the light falling on the subject from reading-lamp "F" Not being diffused, it will give us a harder, snappier light The respective distances between the subject and lamps "A" and "B" can be balanced so as to get any desired light-balance Bear in mind, of course, that the light from lamp "B" should naturally be a bit the more intense, as that is to be the high-light side of the picture

Now, our picture will show a little of the room beyond, so there will have to be some light there If you are getting enough of the room in your picture to warrant it, it might be advisable to cast some shadow-patterns on its farther wall, with Photoflood units However, the first thought we have when we think of an illuminated room in the distance is that some light must stream out Therefore we take lamp "C," another 500-watt unit, and place it as shown, using a diffuser if it appears advisable As the sketch shows, it will give us the patch of light apparently streaming out from the back room, and also a nice edge-lighting (or back-light) on the edge of the curtains

On the wall behind the subject, there is a wall-fixture, which we will assume is fitted with ordinary, flame-tinted 25-watt globes We can turn these on—not for actual illumination, to be sure—but for the natural effect their glow will give To heighten this, we can place a diffused spotlight on the mantelpiece focused on the wall-fixture, so that it gives us precisely the patch of light that such lamps cast on the wall behind them—but (thanks to the spotlight) raised to photographable intensity. Now, in reality, such a wall lamp would have an effect upon the furniture in front of it—and of course, upon the people, too This result would be an edge-light or backlight: so we simulate this by placing a Photoflood unit—lamp "D"—in line between the chair and the wall-fixture, and in such a position that it is screened from the camera by the book-table This will give us the effect we want—a back-light on the edges of the chair, table, and subject which will separate them from the background Lamp "D" should be as high off the floor as is practicable, and well behind the subject Remember, we are shooting with a 15mm lens and at this distance our vertical field is 3 4 feet; we will naturally cut the picture some little distance from the floor. Therefore, we can, if necessary, put lamp "D" right on the floor, and it would probably be out of the picture but we will get a better effect if it is raised a couple of feet from the floor, and masked by the table If we include the legs of the table, this lamp can be placed at such an angle, that, while still doing its primary work, it will also give us a back-lit effect along these legs

The main source of our apparent light is, of course, reading-lamp "F" We can deal with this as seems most advisable. either putting a Photoflood into it, and using it as part of our bona-fide lighting, or merely putting a moderately strong bulb (say 150 watts) into it, simply to suggest that it is a major light-source, and letting the actual light come from lamp "B"

"I Took a LEICA to the Stratosphere" says

JEAN PICCARD

"The pictures we took came out very well. I am very content with the results. For making photographs of the instruments inside the gondola I appreciate specially the unusual focal depth of the Leica camera. The possibility of taking many pictures without having to reload the camera is always an additional asset."

A Precision Camera Perfectly Adapted to Every Photographic Requirement

LEICA is unequalled for speed, convenience, and versatility of performance Built-in range finder coupled with lens for automatic focusing Focal-plane shutter with all speeds from 1 to 1/500th second, including all S-L-O-W speeds. 11 Interchangeable Lenses, including speed lenses, wide angle lenses, tele lenses and others Uses Cinema film, clear enlargements up to 12x18 inches or more Price $88 50 and up Write for free illustrated booklet

The Autofocal

LEICA

U S Patent No 1,960,044

E. Leitz, Inc., Dept. 637

60 East 10th St., New York City

"SUPERSOUP"

The Fine Grain Developer

$1 25 for 32 ozs.

Mail order miniature finishing service a specialty

Morgen Camera Shop

6305 Sunset Blvd , Hollywood, Calif

TRICKS and GADGETS

● For the past two months this department was replaced by the description of the trick titler by Ed Lucas That was a contribution by Lucas to the Tricks and Gadgets contest

We have such a wealth of material submitted it is going to take us several months to catch up with the supply

Film Viewer

Here's a mighty practical gadget and at the same time one that can be built by almost anyone, whether he is handy with tools or not.

It was submitted by J D Cochrane of North College Hill, Ohio. Cochrane tells us of other interesting things he has built, but submits his View Finder in the contest.

If you will study the photograph and little sketch as we describe this gadget we are sure you will realize that it can be built by anyone who owns a saw and a few other tools

The first thing you will need is a light source Cochrane used a small reading light, the type which clamps to a book This as you know comes equipped with a reflector If you will look at the photo you will be able to see the electric wire leading in from the right edge of the photo

Next a condenser is necessary If you haven't one you can purchase one from Eastman Kodak Company Cochrane used one he had in an old Model C Kodoscope This condenser you will have to place in front of your light source, but back of your film Look at your projector and you will see in what order these things are used You will find a reflector, the light, a condenser, then your film gate, and then your projection lens

Next in order Cochrane placed a piece of frosted glass to give a diffused light and also to protect the film from excessive heat coming from the light source

A film gate was the next item in order This you will note from the little sketch is made up of layers of polished metal, bakelite or heavy film It is through this gate that the film is conveyed, touching only the outer edges of the film, thereby eliminating the possibility of scratching the emulsion or film This slide or guide will give you the desired width, you, however, will have to mask off for the height so as to take in only one frame at a time You can build the mask from the same material you use for constructing the guide, you lay this mask, however, on top or below the guide

Next you will need a lens This you merely take from your projector. In other words your projector lens will live a double life It will continue to serve



on the projector and will double on your viewer You will have to mount this in such a way that it can be raised or lowered for focusing

The last piece for the viewer is the frosted or ground glass on which the picture will be viewed You will note from the picture that this was attached very simply This glass has only one upright support, a board on the left Cochrane did not box this in, the three sides are left open and the glass fitted on top with a frame of some sort

So as to use this with his rewinds he built a special support for a 400-foot reel as shown on the right of the photo In view of the fact that this support does not have to have a rewind it will not be difficult to make as it will merely be necessary to have an upright piece and a peg of some sort on which to place the reel

The framework of the viewer is basically two pieces of board, one at the bottom for the main support and one at the side to support the ground glass used for the screen A simple angle-iron mounting will permit you to place this at any angle you desire These angle-irons secured at any 5 and 10 can be bent easily

While this is not a beautifully finished viewer, still it is practical Care should be taken in building that portion which makes up the guide and gate and the method used to bring it toward the other rewind The photo would indicate that Cochrane has used a roller on that side Whether this is made up of an ordinary spool or something else is hard to determine, but it would be well to have a roller of some sort at this point, and depending upon the angle of this viewer, to have one at the other side so as not to scratch the film

Home-Made Humidor Can

J R Newhart of Milwaukee writes in how he has made a humidor can from some of the old 400-foot 16mm positive cans which he had on hand These cans are not made with humidors Newhart secured a small supply of copper screening, the kind used on doors and windows. He selected copper as this will not rust

Next he purchased some liquid solder This can be secured from the 5 and 10 for 10c In addition to this he merely needed either strong scissors or tinsnips He tells us he bought a pair of tinsnips from the 5 and 10 for 15 cents, and that the screen wire cost him 12 cents From this wire he made 8 humidor cans

This was his method He cut a piece of screening the size he wanted for the bottom of the can He cut a piece of blotting paper smaller than this wire, then he placed the wire over the blotting paper in the bottom of the can, applied the liquid solder to the edges of the wire, and he had a humidor can

The reason for fastening the wire was so that it would not fall out every time the can was turned over Of course, it is not necessary to fasten this wire, it merely acts as a separator between the reel and the blotter Also this wire can be cut oblong and fastened at each end only, so that new blotters can be placed under it from time to time

SOUND-ON-FILM
• RENTAL LIBRARY •
A large variety of subjects always available. Comedies, Dramas, Cartoons, Educational Subjects, etc
Send self-addressed, stamped envelope for list of subjects
Visual Instruction Supply Corp.
1757 Broadway Brooklyn, N. Y.

KIN-O-REEL
16mm 400-ft., 1200-ft. and 1600-ft. solid aluminum reels.
KIN-O-DOR
The ideal humidifying can for your films Prices to Dealers on Application.
KIN-O-LUX Inc., 105 W 40 St NEW YORK

The New 16mm
PANCHROMATIC NEGATIVES
(Eastman, Agfa, Dupont)
will surprise you with their fine quality, their beautiful tones and grainless reproductions if you have them developed by the
DUNNING GRAINLESS METHOD
DUNNING PROCESS COMPANY
932 N. La Brea Avenue
Hollywood, Calif.
(35mm reduced to 16mm)

15% CASH DISCOUNT
Motion Picture Equipment
Between January 1st and February 15th is your chance to save money. On standard new items from Victor Animatograph, RCA, Weston Meters, Haile Brod-Lites and distinctive Titles. No trade-ins, straight cash.
Act Today
J. C. HAILE & SONS
MOTION PICTURE DEPT.
215 Walnut St. Cincinnati, Ohio

TITLES •
WITH THAT "FINAL TOUCH"
Give your pictures that professional finish you have always wanted to attain ART TITLES provide clear, clean, crisp type set in deep, black backgrounds with clever borders Cost per title (16mm only) 5 words or less, 25c, extra words 3c each. Minimum order $1 Send for FREE samples and descriptive literature
ART TITLE GUILDE
5519 Broadway Chicago

There is yet another possibility open to us in some cases, for getting our back-lighting—from the ostensible source of the wall-lamp. This is to hang a lighting unit, professional-style, from the moulding on the wall It would replace lamp "D," of course, or supplement it, if we want that lamp's effect on the table-legs It would naturally have to be inclined in such a way as to avoid directly striking the camera lens, and a deep lens-hood is always advisable when working with artificial lights When using this method, remember that you can do a great deal with such lights which while they may be in front of the camera, are actually out of the area being photographed

The photographic illustration, aside from giving an idea of how professional sets are made to order for photography, and giving some hints as to this type of lighting (note the "baby" spot on the wall, in the same service as our lamp "E"), also illustrates a point we have not as yet mentioned this is the highlighting of the picture on the wall You will notice, just over the portrait of Queen Victoria, a "Baby Spot" (not diffused, but well "flooded out") which is hung on the wall just outside the camera-line, so that its beam strikes down across the picture, high-lighting it and its frame—and also the door-frame beyond This is a useful idea for emphasizing any particular feature of a room Similar methods can easily be adopted to the individual requirements of the amateur

Equipment Prizes Awarded

Continued from Page 24

Robert F. Gowen, Ossining, N Y, for his picture "The Menace"

Frank Gunnell, Staten Island, New York, for his picture "From Winter Snows to Summer Sunshine"

Howard J Hargraves, Chicago, Ill, for his picture "Dark Horizon"

Duncan Mac D Little of New York City for his picture "Circus"

Dr Donald H Miller, San Leandro, Calif, for his picture "Hobby Within a Hobby"

Walter Mills, Grand Rapids, Mich, for his 8mm picture "Noon Hour"

Sylvanus F Nye, Kenmore, New York, for his picture "Christmas 1933"

THE IDEAL FILM
Try this economically priced film You will be satisfied with the results and the savings you achieve

No 1—100 ft in green box $3.00
No 2 100 ft in red box 3.50
Prices include Processing, Scratch-Proofing and return postage
KIN-O-LUX, Inc.
107 West 40th Street New York

HUGO MEYER LENSES

HUGO MEYER & CO.
245 WEST 55TH ST NEW YORK

CRAIG JR. SPLICER $3.50
Now available for use with both 8 mm and 16 mm films.



CRAIG SPLICER $10
Now available in 16 mm size for use with either silent or sound on film films

CRAIG MOVIE SUPPLY CO.
1053 So. Olive
LOS ANGELES, CALIFORNIA
Represented by Ampro in the East

SCREENS - REFLECTORS & PROJECTOR CASES
Perfection in Projection
Perfection in Projection
BRITELITE TRUVISION
portable projection screens
MOTION PICTURE SCREEN & ACCESSORIES CO.
49-51 WEST 24TH STREET NEW YORK CITY
WATKINS 9 - 2876
DELUXE "A" MODEL 30x40 $15.00 list
Other sizes in proportion Write for literature and prices on all models At all Dealers

AN ADVERTISEMENT
BY
AMPRO MODEL A OWNERS

Here are a few excerpts from numerous letters in our file.

The Ampro is suitable for large auditoriums. Read this letter.

No. Edmonton, Alta. Can
Franciscan College,
"I recommend the Ampro Model A Projector for parish halls and high schools for visual education."
Sincerely,
Fr. Alphonse Claude

Bass . . . Cine Headquarters . . . sold more 16 mm projectors in 1934 than in the peak years of '28 and '29. Significant!

The Ampro is easy to operate. Read this letter.

Cobleskill, N. Y.
"The Ampro Model A is a fine machine, easy to operate. I am much pleased with it."
Yours truly,
F. H. Ryder.

You will be satisfied with the Ampro Model A.

DOLLAR FOR DOLLAR

The Ampro Model A is the best value money can buy. Fifteen points of superiority. 400 watt long-life Biplane Mazda equal in illumination to 500 watt . . High power cooling . . 10½ to 1 kickback movement . . High speed auto rewind . . Die-cast machined body . . Centralized lubrication . . Centralized controls . . Fibre gears . . Still picture feature . . Forward and reverse . . Venturi type aluminum chimney cooler . . Oversized motor - largest in any projector . . Licensed for Kodacolor . . Light in weight . . Beautiful in appearance . . Ampro exclusive tilt.

You can buy this fine instrument complete with case, ready to use factory guaranteed for a year - a true $135.00 value - nothing near it for almost double the money $99.50

ORDER FROM THIS AD.

WRITE FOR FURTHER DETAILS AND BASS BARGAINGRAM.

MORE LIVE DEALERS WANTED WHO KNOW GOOD VALUE.

Bass will refund your money if not satisfactory.

BASS CAMERA COMPANY
179 W. MADISON ST. - CHICAGO, ILL.

R F Oder Pasadena, Calif., for his 8mm picture "Symphony Mechanicus"

Dr G L Rodenburg, New York City, for "The Butterfly"

Alvin D Ross, New York City, for "Interlude Between Acts"

K G Stephens, San Francisco, Calif., for "Holiday"

Freemon F Taylor, Llonerch, Pa., for "Zoorilla"

K Tsukamoto, Japan, for "An Alpine Conquest"

H W Voss, Ft Meyer, Flo, for "Florido Montage"

E W. Walker, Beverly Hills, Calif., for "Death Volley"

L Clyde Andersan, Salt Lake City, Utah, "Canyons of Romance"

W R Anderson, Salt Lake City, Utah, his 8mm picture "Our Family Album"

H M Armstrong Cape Cottage, Me., for "The Coming Farth of A Notion"

E M Barnard, Kansas City, Mo., for "Christmas, 1932"

Lawrence Legg, Council Bluffs, Io., for "Us Guys on Vacation"

Y Kaneko, Japan, for "A Fishing Village"

F C Ells, Yokohomo, Japan, for "Tombo"

Vincente Mills, Manila, P.I., for "Flogellotion in the Philippines"

Nemo, London, England, for "A Doy Excursion"

J B S Thubron, Fleet, Honts, England, for "Her Second Birthday"

LET'S TALK ABOUT LENSES

Continued from Page 27

And now for a word on suggesting the right focal length telephotos for your jobs Many cinephotographers find the 2" telephoto (sometimes also called a "long focus" lens) very well suited to such things as street scenes Its included field is just half as high and half as wide as that of the 1" lens, and is regarded as a connecting link between the normal 1" and the telephoto series Perhaps the most popular telephoto lens is the 3", because its field is such as to appreciably magnify distant objects, such as the players of a football team, and because of its relative cheapness compared to still longer telephotos Also, it is possible to obtain a fair picture with the 3" telephoto even tho the camera is hand-held

Beyond the 3" are the 3½", the 4", the 6", and now comes the latest thing in telephotos—the 10", 12", and 14" telephotos Except for special work, which the average amateur may never even dream of encountering, anything over a 6" lens on a 16mm camera is to be bought with our eyes wide open to the extremely ominous possibilities of blur thru wobble of the camera, even tho it be used on a tripod Even the most rigid of tripods will transmit vibrations too slight for us to notice to a camera, and the longer the focal length, the more trouble we're likely to get into from jumpy pictures

Perhaps you've noticed that there seems to be a form of "distortion" in your films made with any lens other than the normal 1" 16mm lens or the ½" 8mm lens A shot made with the wide-angle lens has the peculiar flat appearance of a Brownie camera picture, and shots made with telephotos don't seem to have the proper "perspective" You've no doubt noticed, even on the professional screen, that a telephoto shot of, say, a landing airplane shows the plane practically the same size several hundred feet away from the camera as it does fifty feet away

I thought we'd get around to discussing this "distortion" this month, but inasmuch as the effect in cinephotography is really tied up with projection, suppose we defer the matter until next month's concluding article of the lens series If you've been reading articles on lenses lately and have been led to believe that there is no such thing as distortion in viewing, please draw up a chair at next month's session and prepare to watch the fireworks See you then.

Formula for Reversing Film

Continued from Page 28

Immerse the film in this until the parts formerly densest become quite transparent If there are found to be dark spots on the film, reversion is not complete, rinse the film thoroughly and return it to the reversion bath Then wash, and bleach again

The final step is darkening, this is done in a solution prepared by adding 150 grains of Sodium Hydrosulphite (NOT hyposulphite) to the bleaching bath The film is placed in this, and the image steadily darkens until a good, brownish-black positive is produced It is important that the Sodium Hydrosulphite be perfectly fresh otherwise the image may not darken sufficiently, or may turn an unsatisfactory sepia tone

After darkening, the film should be

GOERZ

The professional and amateur alike will appreciate the discriminating select Goerz lenses for their cinematic requirements. The various focal lengths of the Kino-Hypar, Cinegor and Telestar afford a definite lens for every purpose.

Send for 24-page catalog which describes these lenses in detail and which lists such useful devices as the Effect Device and Mask Box, the Variable View Finder and the Reflex Focuser

C. P. Goerz American Optical Co.
317 East 34th Street New York

KIN-O-LITE

for Viewing 16mm, Leica, Miniature, X-Ray and other films.

A Light Box

Complete with lamp, 5-ft. extension cord and attachment plug ready to insert into light socket. $2.00

KIN-O-LUX, Inc.,
107 West 40th Street New York

ANNOUNCEMENT

—•—

A New Three Color Multifilter

Green Yellow — Yellow — Red

All the Essential Filters in One To Use in the Harrison Sunshade

•

HARRISON & HARRISON
645 N. Martel Ave.

Cinematographic Annual Vol. 1

Now $2.50

thoroughly washed in running water—at least 15 minutes—and then dried. Each of these solutions is sufficient for about 30 feet of sub-standard film, although the developer will last for about 90 feet. The quantities given here are those intended for use in the tanks made by the Pathex people in Europe, which hold 26 feet of film (one full Pathex charge). They are not as yet available in America, but may be had either from MM. Pathe-Enseignement, 20 BIS rue La Fayette, Paris, 9e, France, or from Pathescope, Ltd., 5 Lisle Street, London, W.C.2., England. The solutions recommended can, of course, be made up in any larger quantity for use in larger tanks. Incidentally, the chemical type of reversion does not require a solid drum developing system.

With regard to the processing of reversal film by individual amateurs, most of the manufacturers state that while methods outlined above will work with their products, they do not recommend individual processing, as an individual is rarely equipped to exercise the same exact control of all operations that the regular processing stations do. If an individual feels it is necessary to process his own film, the manufacturers point out that far more satisfactory results can be obtained by developing the film (reversal or otherwise) as a NEGATIVE and subsequently making prints from it.

Wheels of Industry

Continued from Page 30

16mm Recording Unit

● The Hollywood Motion Picture Equipment Co. announces a very small recording unit for 16mm cameras that consists of a glow tube about as big around as a pencil and one inch long, an amplifying set made up of one tube using a 2-volt battery. These items, together with the B battery and microphone, make up the entire Recording Unit.

Present plans are to sell the unit to the individuals and they to have local machinists fit them to their existing cameras.

16mm News Reel

● Peerless Cine News, America's only 16mm newsreel, will release its first issue early in January. Among the outstanding news events, unusual and novelty subjects featured in this first release are:

The Tournament of Roses Parade at Pasadena and the New Year's Rose Bowl Game between Stanford and Alabama, intimate shots of Huey "Kingfish" Long and Mrs. Long enjoying a long-delayed honeymoon, modern "49'ers" earning a living by panning gold in the famous Mother Lode country of the "gold rush" days, a turkey that is bigger than a horse, a recently discovered elephant-

Sound Specialists

16mm

Cameras
Recorders
Recording
Projectors
Dual Turntables
Complete Studio
Amplifiers and Microphones
Single System Sound Pictures
Double System Sound Pictures
Sound Added to Silent Pictures

CURRENT SPECIALS

RCA Photophone 16mm sound projector. New tested machines in original factory cartons $105

Standard dual turntable outfit, with amplifier and microphone, complete in two portable cases $109.50

Deluxe dual turntable, with crystal pickups, crystal microphone, amplifier and two speakers in portable carrying cases, 7½ watts output $206.50

Motion picture and sound equipment for any purpose designed and built, repaired or improved

G. A. BUSCH & COMPANY
33 WEST 60TH ST. NEW YORK
Phone Clr 7-2400



Announcing

America's Only 16mm News Reel

Peerless Cine News

A 400-foot reel of national and international news events, educational and nature subjects, historical events, doings of famous people, novelty stunts, oddities and unusual material. A reel of the most diversified short subjects yet offered the public.

Released once each month in both SILENT AND 16MM SOUND ON FILM

Ask to see

Peerless Cine News

At your dealers.
Literature on request.

PEERLESS MOTION PICTURE INDUSTRIES
1327 N. Highland
Hollywood, Calif.

Fotoshop Film Specials

16mm 100-foot rolls

Super Speed Panchromatic	$3.79
Super Sensitive (Neg and Pos)	5.50
Panchromatic (Neg and Pos)	4.75
Regular Ortho	2.75

These prices include processing and return of film to you Our regular guarantee—a new roll replaced free of charge if you are not satisfied—applies

We can supply any make of negative film you may desire—Eastman Agfa, Dupont Gevaert at these same prices

FOTOSNOP LABORATORY SERVICES

TITLING EDITING
REVERSING PRINTING
Duplicating and Fine Grain Developing

FOTOSHOP, INC.
136 W 32 St, New York City

CAMERA CRAFT

A MONTHLY MAGAZINE OF PHOTOGRAPHY

William A Palmer is Editor of our new Cinema Department

He is an ardent amateur who knows his hobby from A to Z.

•

Send your movie problems to him

•

SEND 25 CENTS FOR A LATE COPY

•

CAMERA CRAFT
PUBLISHING COMPANY
703 Market Street
San Francisco, California

CLASSIFIED ADVERTISING

Rates Seven cents a word Minimum charge, one dollar per insertion

FOR SALE—MISCELLANEOUS

BELL & HOWELL-Mitchell-Eyemo Cameras, lenses, magazines, tripods, moviolas, splicers rewinds All kinds of sound and laboratory equipment Inquiries invited. CONTINENTAL FILM CRAFT, 1611 Cosmo St., Hollywood Calif Cable address "Tomwhite"

ARTREFVES latest model 1935 portable double sound recording unit with double sprocket recorder automatic aiged control motor, twin fidelity optical unit Latest type camera motor New type microphone Complete factory guaranteed, $2,400 This is the only authentic ArtReeves equipment for sale in Hollywood outside factory Camera Supply Co, Ltd, 1515 Cahuenga Blvd, Hollywood, Calif

MITCHELL STEEL GEAR CAMERA perfect condition, all standard Studio equipment Astro Pan Tachar lenses, net $1450 Camera Supply Co, Ltd, 1515 Cahuenga Blvd, Hollywood, Calif

LENS CAPS—Non-tarnishing, alloy Attractive- For all types of 35mm or 16mm lense $2 00 Slip-over diameter required when ordering R E. STUART CO, 4139 N Meridian Indianapolis, Ind J

TWO USED Powers 35mm projectors complete with Mazda equipment and Cinephor condenser One Moon enclosed motor-driven rewind W Chas. Swett, 705 Hollywood Security Bldg, Hollywood, Calif HO 5893.

8 400-ft reels and 3 Humidor Cans., all for $2 25 plus postage Fotoshop, Inc, 136 W 32nd St., New York City T

LIKE NEW—Sound Moviola Model UC, price $450 00 Also new H C E free-head and legs for Bell & Howell, Eyemo or DeVry portable cameras, $75.00 complete. Hollywood Camera Exchange, 1600 Cahuenga Blvd., Hollywood Calif

IN GOOD condition, Bell & Howell Camera 120-degree, three lenses, four 400-ft magazines, tripod, carrying case complete—$550 Hollywood Camera Exchange, 1600 N Cahuenga Blvd., Hollywood Calif

LIKE NEW Mitchell Camera silenced Academy aperture, Pan Tachar lenses tree head tripod 1000-ft magazines, complete—$2000 Hollywood Camera Exchange, 1600 N Cahuenga Blvd, Hollywood, Calif

LIKE NEW, Artreeves portable double sound recording outfit with Bell & Howell Silenced camera, complete in every detail A real bargain, price $3500 Price without camera, $2500 Hollywood Camera Exchange, 1600 N Cahuenga Blvd, Hollywood, Calif Cable address HOCAMEX

WANTED

MOTION Picture—Still Picture Laboratory and Cutting Room Equipment — Lenses Finders Tripods, Highest prices paid CONTINENTAL FILM CRAFT, 1611 Cosmo St Hollywood, Calif

MOTION Picture and Still Cameras, all types Lenses, Finders, Tripod Heads Leica or Contax Cameras Cash for bargains Camera Supply Ltd., 1515 Cahuenga Blvd, Hollywood, Calif

WANTED—Number 1 Eastman Stereopticon camera. Harry Perry, OXford 1908

WANTED—Daylight Developing tank for 3¼-x4¼ cut film Box 246, American Cinematographer, 6331 Hollywood Blvd, Hollywood, Calif

WILL PAY CASH FOR Bell & Howell, Mitchell, Akeley or DeBrie Cameras, lenses, motors parts and accessories Motion Picture Camera Supply, Inc, 723 7th Ave, New York, New York. T

MISCELLANEOUS

WE BUY—sell or rent everything necessary for the making — taking — ar showing of motion pictures. Sound or Silent — 35mm and 16mm. We specialize in equipping expeditions Ruby Camera Exchange, 724 7th Ave, New York City. T

INTRODUCTORY Offer 8mm subjects, 50-ft reels, $1 50 Interesting variety of subjects now available Also 16mm sound and silent film Sales rentals and exchanges Harry Mendelwager 311 West 50th St, New York, New York

shaped fungus, national championship auto races and other interesting short subjects

Peerless Cine News will be released once each month in both silent and 16-mm sound-on-film and will contain news events of national and international importance, historical events, odd and interesting people and places, human interest stories and educational subjects.

PHOTOGRAPHIC ANNUAL

The 1935 Annual has been issued by the American Photographic Publishing Company

This year's edition contains much for the miniature camera user One article that will undoubtedly interest is by John Lonctot on "The Control of Graininess" The artistic side is recognized by such articles as "Line and Tone as Expressive Factors in Composition" by William S Davis "Home Portraiture with the Miniature Camera" is the subject handled by E T. Howell

Focus in Cine Work and Cinema Evidence in Courts will undoubtedly interest those in amateur movie activity

Other interesting articles are "A Universal Focal Slide Rule," "Filters in Press Work," "Notes on Infra-Red Photography," "Possibilities with Photoflash Lamps," "Standard Darkroom Procedure," "Home Portraiture with Miniature Camera," "Pictorial Possibilities in the Portrait Studio," "Night Photography in Natural Colors," "Aerial Photography," and other pertinent subjects

TRICKS GADGETS

Another Contest

Here's how it works. Send us in tricks you have done in filming with your 8mm, 9½mm or 16mm camera. Explain them to us so that we can explain them to others in the pages of American Cinematographer

For every one we publish you will be entitled to your choice of one of the prizes listed below.

By Gadgets we mean little pieces of equipment you have built, designed or devised. Equipment that works. Little gadgets you have added to your camera, projector or otherwise. For instance, we heard of one fellow who built a splicer out of a mouse-trap . . . that's a gadget.

What kind of gadgets have you made . . . what sort of tricks do you do with your camera or equipment? If necessary send us a rough sketch or a snap shot of your equipment if it will help describe it better and quicker.

Here's Your Chance to Win Equipment or Film

Frequently we have published what might be termed tricks. Such as making distorted effects by pouring sweet oil over a glass in front of the film. Others have been published from time to time.

In the way of gadgets we have reported many things from the building of a complete 16mm camera by amateurs down to making their own reels.

What Have You Done?

Here are the prizes . . . you may make your choice of any one of them

- Beltipod
- Filter Holder
- Choice of Filter
- Splicer
- Half-Dozen 16mm Reels
- Half-Dozen 16mm Cans
- 3 Reels and 3 Cans
- 100-ft. Roll of 16mm Pan Film
- Two Rolls of 8mm Film
- 8mm Splicer and Rewind
- Humidor Can Case for 12 Reels
- 22x30 Beaded Screen
- 3 Clamp Lamp Reflectors with 3 Photoflood Lamps
- One Dozen Photoflood Lamps

Send Your Entries to Editor

American Cinematographer

6331 Hollywood Blvd., Hollywood, Calif.

Prosperity for 1935!

Everything points to an industrious and prosperous Year. It is our sincere hope and wish that you will share liberally in that prosperity and that the Mitchell Camera will continue to play its important role in the production of successful pictures

Mitchell Camera Corporation

665 N. ROBERTSON BOULEVARD
WEST HOLLYWOOD, CALIF.

Cable Address "MITCAMCO"

Phone OXford 1051